

Lot #	CFM #	Name	Description
	8216	Stainless steel bin dumper	Stainless steel hydraulic bin dumper, capable of handling bins up to 53" wide x 48" long x 42" tall, 12" bin infeed height, 67" product dump height, narrows from 53" wide to 24" wide discharge chute, 2 HP hydraulic powerpack, approximately 10 gallon capacity, 1755 RPM, wired 208-230/460/3/60, control panel, stainless steel construction, mild steel hydraulic reservoir and cylinders.
1	8124	Stainless steel hydraulic bin dumper	Stainless steel hydraulic bin dumper, capable of handling 4' wide x 53" tall bins, 3' bin bay depth, 49" bin infeed height, approximately 66" bin dump height, 5 HP hydraulic power pack, 1150 RPM, 230/460/3/60, 16" wide x 17-1/2" long x 16" tall tank, 20 gallon capacity, with Allen Bradley Powerflex and manual controls, all stainless steel construction.
2	8121	Stainless steel bin dumper, hopper, and lump breaker skid	Stainless steel hydraulic bin dumper, hopper, and lump breaker skid, capable of handling 53" wide x 52" tall bins, 40" bin bay depth, 41" bin infeed height, 40 gallon hydraulic powerpack, discharges to 58" wide x 48" long x 32" deep hopper, discharges to 16" wide lump breaker with 1-1/2" tall cleats, 42" product discharge height, 2 HP electric motor gearhead drive, 1755 RPM, 208-230/460/3/60, with PowerFlex controls, all stainless steel construction.
3	8250	Stainless steel bulk dump hopper	Stainless steel bulk dump hopper, 2 each 50" wide x 51" long x 13" deep hoppers, 2 each 11" wide x 6" long product discharge with manually operated feed gate, 80" product infeed height, 46" product discharge height, 16" tall front wall, 30" tall side and back walls, 24-1/2" wide x 10" tall hopper inspection hatch, all stainless steel construction.
4	MC32	45" diameter x 162" long stainless steel sizing reel	45" diameter x 162" long stainless steel sizing reel, 2 each different sizing zones, zone one bars are spaced every 2", zone two bars are spaced every 3-1/2", 8" tall spiral throughout reel, 5 HP electric motor gearbox chain drive, 1750 RPM, 208-230/460/3/60, 2 each 18" wide x 60" long x 20" deep hopper discharges, one each 39" wide x 18" long hopper discharge take away conveyor, electric motor drive, all stainless steel construction, on stainless steel stand.
5	8252	58" diameter x 153" long stainless steel reclaim reel	58" diameter x 153" long stainless steel reclaim reel, bars spaced every 1/2", 4" tall ribbon throughout drum, 32" product infeed height, 20" product discharge height, trunnion mounted, 7-1/2 HP electric motor chain drive, 1765 RPM, wired 208-230/460/3/60, all stainless steel construction.
6			

	8219	60" diameter x 15' long dirt elimination reel	60" diameter x 15' long dirt elimination reel, 1/2" wide x 1/2" long square perforations, trunnion mounted, 4 each 12' long lump breaker bars, with 14 each 7" long breaker bars spaced every 10", 87" product infeed height, 68" product discharge height, 2 HP electric motor gearhead chain drive, 1755 RPM, wired 208-230/460/3/60, mild steel contact, stainless steel frame.
7	8220	60" diameter x 15' long dirt elimination reel	60" diameter x 15' long dirt elimination reel, 1/2" wide x 1/2" long square perforations, trunnion mounted, 4 each 12' long lump breaker bars, with 14 each 7" long breaker bars spaced every 10", 45" wide x 67" long infeed chute, 87" product infeed height, 68" product discharge height, 2 HP electric motor gearhead chain drive, 1755 RPM, wired 208-230/460/3/60, mild steel contact, stainless steel frame.
8	8409	30" diameter x 52" long stainless steel reclaim reel	30" diameter x 52" long stainless steel reclaim reel, 1/2" gap between rods, reel suspended by 2 each belts, product discharges to stainless steel discharge chute, waste material discharged to 32" wide x 54" long x 24" deep stainless steel hopper, 2 HP electric motor gearhead drive, 1755 RPM, 230/460/3/60, all stainless steel construction.
9	8276	Stainless steel reclaim reel	Stainless steel reclaim reel, 24" diameter x 48" long with 1/4" diameter perforations, 2" tall cleat running through reel, 1 HP electric motor drive, 1755 RPM, 230/460/3/60, all stainless steel construction.
10	7809	38" diameter x 138" long dirt elimination reel	38" diameter x 138" long dirt elimination reel, 1-1/2" diameter perforations, 4-1/2" tall x 20" long cleats on 16" - 26" spacing, 10" wide x 21" long discharge chute, 60 HP electric motor chain drive, 1760 RPM, wired 208-230/460/3/60, aluminum drum, stainless steel frame.
11	7306	55" diameter x 6' long stainless steel dirt elimination reel	55" diameter x 6' long stainless steel dirt elimination reel, 2-1/2" gap between flat rods, 1-1/2 HP electric motor chain drive, 1715 RPM, requires bearing and stand.

12

13	MC34	Olney flotation washer	Olney flotation washer, model number 1987, serial number 454-05-40, 48" wide x 42" long x 32" deep stainless steel tapered tank, feeds to 42" wide x 87-1/2" long riffle pan destoner, 54" long destoning section, 3-1/4" tall cleats spaced every 1-1/2", lifting lever mechanism used for lifting riffles away from pan for easy cleaning, with discharge chute for stones, product proceeds to 48" wide x 40" long dewatering shaker, 1/8" perforation, requires one section of perforated screen, with 42" wide x 60" long x 18" deep water recirculation tank and mild steel centrifugal pump, all stainless steel construction.
	MC38	Olney flotation washer	Olney flotation washer, model number 1987, serial number 431-0S-40, 48" wide x 42" long x 32" deep stainless steel tapered tank, feeds to 42" wide x 87-1/2" long riffle pan destoner, 54" long destoning section, 3-1/4" tall cleats spaced every 1-1/2", lifting lever mechanism used for lifting riffles away from pan for easy cleaning, with discharge chute for stones, with mild steel centrifugal recirculation pump, all stainless steel construction, requires dewatering shaker and recirculation tank.
14	8097	Stainless steel flooded wash tank and elevator	Stainless steel flooded wash tank and elevator, 48" wide x 48" long x 48" deep tank area before elevator, 48" wide x 16' long stainless steel blancher style belt with 1" x 3/4" perforations, 3 each paddle product agitators, 16" diameter with 16" tall cleats, 2 HP electric motor gearhead chain agitator drive, 1755 RPM, 208-230/460/3/60, 62" product infeed height, 64" product discharge height, 6" flanged side bottom fitting, 4" Tri-Clover fitting under discharge conveyor, all stainless steel construction, requires conveyor drive.
15	8098	Stainless steel flooded wash tank and elevator	Stainless steel flooded wash tank and elevator, 48" wide x 48" long x 48" deep tank area before elevator, 48" wide x 16' long stainless steel blancher style belt with 1" x 3/4" perforations, 3 each paddle product agitators, 16" diameter with 16" tall cleats, 2 HP electric motor gearhead chain agitator drive, 1755 RPM, 208-230/460/3/60, 62" product infeed height, 64" product discharge height, 6" flanged side bottom fitting, 4" Tri-Clover fitting under discharge conveyor, 2 HP electric motor gearhead chain conveyor drive, 1755 RPM, 208-230/460/3/60, all stainless steel construction.
16	8284	Stainless steel flooded wash tank and elevator	Stainless steel flooded wash tank and elevator, 48" wide x 140" long x 48" deep wash area, 3 each paddle product agitators, 46" wide with 6" tall paddles, 36" wide x 124" long thermoplastic conveyor, 2 HP electric motor drive, 1725 RPM, 230/406/3/60, 49-1/2" product infeed height, 66" product discharge height, all stainless steel construction.
17			

8101	Stainless steel submersion tank and elevator	Stainless steel submersion tank and elevator, 24" wide x 14' long x 16" deep submersion tank with blancher belting, 2 HP electric motor gearhead drive, 1755 RPM, 230/460/3/60, conveyor discharges to 24" wide x 12' long cleated elevator with blancher belting, 1/4" tall cleats spaced every 26", 2 HP electric motor gearhead drive, 1755 RPM, 230/460/3/60, 32" wide x 20" long x 20" deep recirculation tank, 64" product infeed height, 74" product discharge height, all stainless steel construction.
18		
7817	36" wide x 11' long stainless steel wash elevator	36" wide x 11' long stainless steel wash elevator, 58" wide x 36" long x 21" deep infeed hopper, 36" wide x 11' long stainless steel mesh belt elevator, 8 each 27-1/2" long x 1-1/2" tall cleats, randomly spaced, 36" wide x 36" long discharge chute, 63" discharge height, 2 each 1" diameter x 36" long spray manifold, 9 total spray heads, 60" wide x 24" long x 30" deep water recirculation tank, 12" straight pipe with 3 propeller forced debris discharge, 1 each 6" flanged connection with butterfly valve, 1 each 2" threaded connection with ball valve, 1 each 4" threaded drain connection, 2 each 4" threaded side connections, 2 each 8" wide x 8" long clean out hatches, all stainless steel construction, requires all drives.
19		
8257	Stainless steel flooded wash tank	Stainless steel flooded wash tank, 48" wide x 18' long x 36" deep "W" shaped bottom reservoir, 5 each 6" wide x 46" long paddles drums, all drums chain driven by 2 HP electric motor, 1725 RPM, wired 208-230/460/3/60, 36" wide x 7' long product discharge conveyor, 1" diameter x 44" long spray manifold with 1/8" diameter perforations, 56" product discharge height, 1 each 8" middle side straight pipe connection, 2 each 4" threaded bottom side drains, all stainless steel construction, requires discharge conveyor belting.
20		
8132	36" wide x 58" long Olney riffle pan destoner and tank	36" wide x 58" long Olney riffle pan destoner and tank, 1-1/2" tall angled riffles, lifting lever mechanism used for lifting riffles away from pan for easy cleaning, manually controlled cranks to lift and lower riffle pan, 48" wide x 88" long x 35-1/2" deep tank, 36" wide x 6' long stainless steel wire mesh incline conveyor, 2 HP electric motor gearhead conveyor drive, 1725 RPM, 2300/460/3/60, side trash cleanout chute with perforated basket, all stainless steel construction.
21		
8259	36" wide x 58" long Olney riffle pan destoner and tank	36" wide x 58" long Olney riffle pan destoner and tank, 48" wide x 43" long x 54" deep sloped bottom product infeed hopper, approximately 50 cubic foot capacity, sloped to 12" wide x 12" tall discharge with adjustable feed gate, 36" wide x 56" long destoner pan, 2-1/2" tall riffles, 47" wide x 89" long x 36" deep tank, 2 each 4" threaded tank infeeds, 6" Tri-Clover tank discharge, 12" wide x 10" long debris collection basin, manual height adjustment, 36" wide x 90" long thermoplastic cleaned product discharge conveyor, 57" product discharge height, electric motor gearhead belt drive, all stainless steel construction.
22		

23	MC33	36" wide x 58" long Olney riffle pan destoner and tank	36" wide x 58" long Olney riffle pan destoner and tank, 1-1/2" tall angled riffles, lifting lever mechanism used for lifting riffles away from pan for easy cleaning, 48" wide x 88" long x 35-1/2" deep tank, 36" wide x 5' long incline and 4' long flat stainless steel thermoplastic incline conveyor, 36" wide x 8" long product magnet over incline, 2 HP electric motor gearhead conveyor drive, 1725 RPM, 2300/460/3/60, side trash cleanout chute with perforated basket, all stainless steel construction.
24	8222	24" wide x 100" Olney stainless steel riffle pan destoner	24" wide x 100" Olney stainless steel riffle pan destoner, 2" tall angled riffles, lifting lever mechanism used for lifting riffles away from pan for easy cleaning, 25" wide x 89" long x 22" deep tank, 200 gallon capacity, 24" wide x 4" long x 6" deep overflow catch basin, 4" Tri-Clover bottom side infeed, 4" flanged bottom side drain with butterfly valve, 2-1/2" threaded middle side connection, float level control, all stainless steel construction.
25	8273	Key model 8 air cleaner	Key model 8 air cleaner, model # 43884-1, serial number 07-171202-1, 60" wide product area, 15 HP electric motor belt drive, 1760 RPM, 208-230/460/3/60, with manual controls, all stainless steel construction, requires infeed shaker and drive.
26	8274	Key model 8 air cleaner	Key model 8 air cleaner, model # 43884-1, serial number 07-171202-2, 60" wide product area, 15 HP electric motor belt drive, 1760 RPM, 208-230/460/3/60, all stainless steel construction, requires controls, infeed shaker and drive.
27	8275	Key model 8 air cleaner	Key model 8 air cleaner, model # 432786-AAAAA, serial number 05-143840, 60" wide product area, 15 HP electric motor belt drive, 1760 RPM, 230/460/3/60, with manual controls, all stainless steel construction, requires controls, infeed shaker and drive.

	8282	Lyco air cleaner	Lyco air cleaner, serial number AC129919070-01, 32" diameter fan, 15 HP electric motor belt drive, 1170 RPM, 208-230/460/3/60, all stainless steel construction, requires shaker infeed, product discharge, and trash discharge chute.
28	8283	Lyco air cleaner	Lyco air cleaner, serial number AC129919070-02, 32" diameter fan, 15 HP electric motor belt drive, 1170 RPM, 208-230/460/3/60, all stainless steel construction, requires shaker infeed, product discharge, trash discharge chute, and fan blades.
29	8108	14" diameter x 7' long stainless steel screw conveyor with hopper	14" diameter x 7' long stainless steel screw conveyor with hopper, 48" wide x 6' long x 14" deep straight wall hopper with additional 26" deep slope, 116" product infeed height, 57" product discharge height, 14" wide x 17" long product discharge, 5 HP electric motor gearhead drive, 1750 RPM, 230/460/3/60, all stainless steel construction.
30	8109	12" diameter x 7' long mild steel screw conveyor with hopper	12" diameter x 7' long mild steel screw conveyor with hopper, 4' wide x 6' long x 46" deep hopper, 99" product infeed height, 54" product discharge height, 9" wide x 20" long discharge, electric motor drive, with inspection platform, stainless and mild steel construction.
31	8122	12" diameter x 8' long stainless steel screw conveyor with hopper	12" diameter x 8' long stainless steel screw conveyor with hopper, 4' wide x 6' long x 13" straight wall with additional 28" deep slope hopper, 87" product infeed height, 38" product discharge height, 11" wide x 19-1/2" long screw discharge, 2 HP electric motor drive, 1750 RPM, 230/460/3/60, all stainless steel construction.
32			

33	8125	6" diameter x 10' long stainless steel screw conveyor with hopper	6" diameter x 8' long stainless steel screw conveyor with hopper, 4' wide x 5' long x 14" deep straight wall with additional 31" slope hopper, 92" product infeed height, 41-1/2" product discharge height, 12" diameter screw trough, 4-1/2" wide x 6" long product discharge, 2" Tri-Clover fitting at base of the screw, 2.5 HP electric motor gearhead direct drive, 1740 RPM, 230/60/3/60, all stainless steel construction.
34	8127	6" diameter x 8' long stainless steel screw conveyor with hopper	6" diameter x 8' long stainless steel screw conveyor with hopper, 4' wide x 4' long x 26" straight wall with additional 26" slope hopper, 7' product infeed height, 39" product discharge height, 12" diameter screw trough, 5" wide x 6" long discharge chute, 2 HP electric motor gearhead direct drive, 1740 RPM, 230/3/60, all stainless steel construction.
35	8223	11" wide x 83" long stainless steel distribution shaker and hopper	11" wide x 83" long stainless steel distribution shaker, 48" wide x 48" long x 28" deep tapered product infeed hopper, 71" product infeed height, adjustable hopper discharge gate, from 0" to 6", 11" wide x 83" long solid stainless steel distribution shaker pan, 6" tall sides, 27" product discharge height, shaking eccentric, 2 HP electric motor belt drive, 1775 RPM, wired 208-230/460/3/60, all stainless steel construction.
36	8226	11" wide x 127" long stainless steel distribution shaker and hopper	11" wide x 127" long stainless steel distribution shaker with hopper, 52" wide x 97" long x 27" deep tapered product infeed hopper, 122" product infeed height, 11" wide x 127" long solid stainless steel distribution shaker pan, adjustable hopper product flow gate, 75" product discharge height, 2 HP electric motor belt shaker drive, 1750 RPM, wired 208-230/460/3/60, 24" wide x 100" long operators platform with handrails, 82" platform height, all stainless steel construction, requires ladder to operators platform.

	8249	10" wide x 65" long stainless steel distribution shaker with hopper	10" wide x 65" long stainless steel distribution shaker with hopper, 48" wide x 48" long x 33" deep product infeed hopper, 89" product infeed height, adjustable product discharge gate from closed to 6" above shaker pan, 49" product discharge height, 2 HP electric motor belt drive, 1750 RPM, wired 208-230/460/3/60, all stainless steel construction.
37	8221	18" wide x 72" long stainless steel conveyor and hopper	18" wide x 72" long stainless steel conveyor and hopper, 48" wide x 48" long x 30" deep product infeed hopper, 96" infeed height, angled to 18" wide x 48" long discharge over 18" wide x 72" long thermoplastic conveyor, 67" conveyor discharge height, all stainless steel construction.
38	MC7	18" wide x 84" long stainless steel dewatering conveyor with recirculation tank	18" wide x 84" long stainless steel dewatering conveyor with recirculation tank, hopper discharge to 18" wide x 84" long perforated thermoplastic belt, 2 HP electric motor gearhead conveyor drive, 1755 RPM, 208-230/460/3/60, 150 gallon recirculation tank, 31" wide x 60" long x 22" deep, various fittings, on stainless steel stand, all stainless steel construction.
39	8244	12" wide x 72" long rubber belted stainless steel conveyor	12" wide x 72" long rubber belted stainless steel conveyor, 6" tall sides, 1 HP electric motor chain drive, 1750 RPM, wired 208-230/460/3/60, all stainless steel construction.

40

	8264	15" wide x 8' long stainless steel rubber belt conveyor	15" wide x 8' long stainless steel rubber belt conveyor, 1 HP electric motor gearhead drive, 1755 RPM, 208-230/460/3/60, stainless steel construction.
41	7891	31-1/2" wide x 106" long inspection conveyor	31-1/2" wide x 106" long inspection conveyor, 38" product infeed and discharge height, 7" wide x 28" long magnet at discharge, 2" clearance over belt, spring tensioned belt scraper at discharge, all stainless steel construction, requires drive, control panel and belting.
42	8182	9-1/2" wide x 5' long stainless steel rigidized feed shaker	9-1/2" wide x 5' long stainless steel rigidized feed shaker, 9" tall sides, 67" product infeed height, 50" product discharge height, 1 HP electric motor belt shaker drive, 1740 RPM, 208-230/460/3/60, all stainless steel construction.
43	8251	14" wide x 97" long Key vibratory stainless steel shaker	14" wide x 97" long Key vibratory stainless steel shaker, dual lane solid shaker pan, 52" product infeed height, 8" tall sides, V-shaped product pan discharge, 16" product discharge height, 2 HP electric motor belt drive, 1750 RPM, wired 208-230/460/3/60, all stainless steel construction.

44

45	MC23	35-1/2" wide x 253" long Key Iso-Flo stainless steel sorting conveyor	35-1/2" wide x 253" long Key Iso-Flo stainless steel sorting conveyor, model number S1022472-1, serial number 10418586, 27-1/2" wide product section with 8" wide sort out lane, 8" tall dividing lane, 1 HP electric motor belt shaker drive, 1760 RPM, 230/460/3/60, all stainless steel construction.
46	MC24	30" wide x 187" long Key Iso-Flo stainless steel distribution shaker	30" wide x 187" long Key Iso-Flo stainless steel distribution shaker, model number 428005-1, serial number 00-51526, 6" tall side walls, 8" long discharges starting at 75" from infeed and 158" from infeed on the right, 2 each 13" wide 16" long x 8" deep discharge chutes, 1 HP electric motor belt shaker drive, 1760 RPM, 230/460/3/60, designed to be suspended, all stainless steel construction.
47	MC25	30" wide x 205" long Key Iso-Flo stainless steel distribution shaker	30" wide x 205" long Key Iso-Flo stainless steel distribution shaker, 6" tall side walls, 8" long discharges starting at 78" from infeed and 168" from infeed on the left, 2 each 13" wide 16" long x 8" deep discharge chutes, 2 HP electric motor belt shaker drive, 1770 RPM, 230/460/3/60, designed to be suspended, all stainless steel construction.
48	MC26	24" wide x 165" long Key Iso-Flo stainless steel distribution shaker	24" wide x 165" long Key Iso-Flo stainless steel distribution shaker, 6" tall sides, 14" long discharges starting at 56" from infeed and 139" from infeed on the right, 1 HP electric motor belt shaker drive, 1725 RPM, 230/460/3/60, all stainless steel construction.

	MC28	24" wide x 194" long Key Iso-Flo stainless steel distribution shaker	24" wide x 194" long Key Iso-Flo stainless steel distribution shaker, model number 425576/1, serial number 98/32591, 12" long discharges starting at 106" from infeed and 173" from infeed on the left, 2 each 13" wide 15" long x 4" deep discharge chutes, 2 HP electric motor belt shaker drive, 1770 RPM, 230/460/3/60, all stainless steel construction.
49	MC29	24" wide x 204" long Key Iso-Flo stainless steel distribution shaker	24" wide x 204" long Key Iso-Flo stainless steel distribution shaker, 6" tall sides, 10" long discharges starting at 28", 112" and 179" from infeed on the left, 1 HP electric motor belt shaker drive, 1760 RPM, 230/460/3/60, all stainless steel construction.
50	8280	8" diameter x 12' long KWS stainless steel distribution screw conveyor	8" diameter x 12' long KWS stainless steel distribution screw conveyor, 2 each 9-1/2" wide x 9-1/2" long pneumatically controlled product drop gates, drops begin at 61" from infeed and 108" from infeed, 74" product infeed height, 55-1/2" product discharge height, 2 HP electric motor chain drive, 1725 RPM, 230/460/3/60, all stainless steel construction.
51	8246	6" diameter x 8' long stainless steel screw elevator	6" diameter x 8' long stainless steel screw elevator, 24" wide x 21" long x 15" deep product infeed hopper, 24" product infeed height, hopper narrows to 4" wide x 6-1/2" long discharge to hopper, 5-1/2" wide x 6" long product discharge chute, 45" product discharge height, 2 HP electric motor gearhead drive, 1740 RPM, wired 208-230/460/3/60, all stainless steel construction.

52

53	8102	9" diameter x 14' long stainless steel screw elevator and hopper	9" diameter x 14' long stainless steel screw elevator and hopper, 48" wide x 8' long x 42" deep hopper infeed, 9" diameter x 14' long stainless steel screw, 66" product infeed height, 24" product discharge height, 1-½ HP electric motor gearhead belt drive, 1740 RPM, 208-230/460/3/60, all stainless steel construction.
54	MC27	24" wide x 22' long stainless steel screw auger	24" wide x 22' long stainless steel screw auger, 8.5" tall screw flights, 26" diameter trough, 3" threaded discharge, chain driven, requires drive and one section of covers.
55	8095	24" wide x 16' long stainless steel screw elevator	24" wide x 16' long stainless steel screw elevator, 23" diameter screw in 24" diameter trough, 24" wide x 24" long product infeed, 18" diameter product discharge chute, 3" threaded side bottom fitting located at infeed of screw, 10 HP electric motor gearhead drive, 3490 RPM, 208-230/460/3/60, all stainless steel construction.
56	8245	9" diameter x 9' long stainless steel screw conveyor	9" diameter x 9' long stainless steel screw conveyor, 10" wide x 9' long trough, 3-1/4" tall flights, 9" wide x 9" long bottom discharge in center of trough, 6" wide x 6" long bottom discharge, 1 HP electric motor gearhead drive, 1740 RPM, wired 208-230/460/3/60, all stainless steel construction, requires trough cover.

57	8410	9" diameter x 32" long stainless steel screw feeder with hopper	9" diameter x 32" long stainless steel screw feeder with hopper, with slotted basin, 38" wide x 20" long x 21" deep hopper with 10" wide x 7" long magnet, 2 HP electric motor gearhead drive, 1755 RPM, 230/460/3/60, on stand, all stainless steel construction.
58	8170	AFC model 25F auger feeder	AFC model 25F auger feeder, serial number M208/A7801-10, built in 2010, 30" wide x 30" long x 20" deep sloped hopper, feeds to 12" wide x 12" long x 7" deep auger feeder, hinged hopper cover and spacer bars, 2" diameter x 6' long auger, 2" Tri-Clover center side hopper fitting, 1 HP electric motor gearhead direct drive, 1740 RPM, 208-230/460/3/60, all stainless steel construction.
59	8171	AFC model 25F auger feeder	AFC model 25F auger feeder, serial number M208/A7801-3, built in 2010, 30" wide x 30" long x 20" deep sloped hopper, feeds to 12" wide x 12" long x 7" deep auger feeder, hinged hopper cover and spacer bars, 2" diameter x 6' long auger, 2" Tri-Clover center side hopper fitting, 1 HP electric motor gearhead direct drive, 1740 RPM, 208-230/460/3/60, all stainless steel construction.
60	8172	AFC model 25F auger feeder	AFC model 25F auger feeder, serial number M208/A7801-2, built in 2010, 30" wide x 30" long x 20" deep sloped hopper, feeds to 12" wide x 12" long x 7" deep auger feeder, hinged hopper cover and spacer bars, 2" diameter x 6' long auger, 2" Tri-Clover center side hopper fitting, 1 HP electric motor gearhead direct drive, 1740 RPM, 208-230/460/3/60, all stainless steel construction.

	8173	AFC model 25F auger feeder	AFC model 25F auger feeder, serial number M208/A7801-5, built in 2010, 30" wide x 30" long x 20" deep sloped hopper, feeds to 12" wide x 12" long x 7" deep auger feeder, hinged hopper cover and spacer bars, 2" diameter x 6' long auger, 2" Tri-Clover center side hopper fitting, 1 HP electric motor gearhead direct drive, 1740 RPM, 208-230/460/3/60, all stainless steel construction.
61	8174	AFC model 25F auger feeder	AFC model 25F auger feeder, serial number M208/A7801-1, built in 2010, 30" wide x 30" long x 20" deep sloped hopper, feeds to 12" wide x 12" long x 7" deep auger feeder, hinged hopper cover and spacer bars, 2" diameter x 6' long auger, 2" Tri-Clover center side hopper fitting, 1 HP electric motor gearhead direct drive, 1740 RPM, 208-230/460/3/60, all stainless steel construction.
62	8176	AFC model 25F auger feeder	AFC model 25F auger feeder, serial number M208/A7801-4, built in 2010, 30" wide x 30" long x 20" deep sloped hopper, feeds to 12" wide x 12" long x 7" deep auger feeder, hinged hopper cover and spacer bars, 2" diameter x 6' long auger, 2" Tri-Clover center side hopper fitting, 1 HP electric motor gearhead direct drive, 1740 RPM, 208-230/460/3/60, all stainless steel construction.
63	8177	AFC model 25F auger feeder	AFC model 25F auger feeder, serial number M208/A7801-8, built in 2010, 30" wide x 30" long x 20" deep sloped hopper, feeds to 12" wide x 12" long x 7" deep auger feeder, hinged hopper cover and spacer bars, 2" diameter x 6' long auger, 2" Tri-Clover center side hopper fitting, 1 HP electric motor gearhead direct drive, 1740 RPM, 208-230/460/3/60, all stainless steel construction.
64			

65	8190	AFC model 25F auger feeder	AFC model 25F auger feeder, serial number M208/A7801-11, built in 2010, 30" wide x 30" long x 20" deep sloped hopper, feeds to 12" wide x 12" long x 7" deep auger feeder, hinged hopper cover and spacer bars, 2" diameter x 6' long auger, 2" Tri-Clover center side hopper fitting, 1 HP electric motor gearhead direct drive, 1740 RPM, 208-230/460/3/60, all stainless steel construction.
65	8191	AFC model 25F auger feeder	AFC model 25F auger feeder, serial number M208/A7801-6, built in 2010, 30" wide x 30" long x 20" deep sloped hopper, feeds to 12" wide x 12" long x 7" deep auger feeder, hinged hopper cover and spacer bars, 2" diameter x 6' long auger, 2" Tri-Clover center side hopper fitting, 1 HP electric motor gearhead direct drive, 1740 RPM, 208-230/460/3/60, all stainless steel construction.
66	8175	AFC model 45F auger feeder	AFC model 45F auger feeder, serial number M208/A7801-15, 30" wide x 30" long x 28" deep straight wall hopper with additional 20" sloped bottom, feeds to 12" wide x 12" long x 7" deep auger feeder, hinged hopper cover and spacer bars, 4" straight pipe hopper cover infeed, 4" diameter x 6' long auger, 2 HP electric motor gearhead direct drive, 1750 RPM, 208-230/460/3/60, all stainless steel construction, requires auger housing.
67	8178	AFC model 45F auger feeder	AFC model 45F auger feeder, serial number M208/A7801-12, 30" wide x 30" long x 28" deep straight wall hopper with additional 20" sloped bottom, feeds to 12" wide x 12" long x 7" deep auger feeder, hinged hopper cover and spacer bars, 4" straight pipe hopper cover infeed, 4" diameter x 6' long auger, 2 HP electric motor gearhead direct drive, 1750 RPM, 208-230/460/3/60, all stainless steel construction.
68			

8192	AFC model 45F auger feeder	AFC model 45F auger feeder, serial number M208/A7801-14, 30" wide x 30" long x 28" deep straight wall hopper with additional 20" sloped bottom, feeds to 12" wide x 12" long x 7" deep auger feeder, hinged hopper cover and spacer bars, 4" straight pipe hopper cover infeed, 4" diameter x 6' long auger, 2 HP electric motor gearhead direct drive, 1750 RPM, 208-230/460/3/60, all stainless steel construction.	
69	8401	Kusel hydrolift elevator	Kusel hydrolift elevator, 18" diameter screw, 97" product discharge height, 48" wide x 15-1/2" long x 28" deep hopper infeed, 38" hopper infeed height, with discharge chute, electric motor drive, all stainless steel construction.
70	6797	Ambec 60" wide x 15-1/2' long stainless steel accumulation table	Ambec 60" wide x 15-1/2' long stainless steel accumulation table, plastic flat belt chain, 41" infeed and discharge height, gearhead chain drive, no side rails, stainless steel construction.
71	MC5	Waukesha model 130 U1 positive displacement pump	Waukesha model 130 U1 positive displacement pump, serial number 1000003219580, 3" Tri-Clover fittings.
72	MC12	Waukesha model 130 U1 positive displacement pump	Waukesha model 130 U1 positive displacement pump, serial number 1000002502232, 3" Tri-Clover fittings, 5 HP electric motor gearhead direct drive, 208-230/460/3/60, on stainless steel base.
73			

	MC11	Waukesha model 134 positive displacement pump	Waukesha model 134 positive displacement pump, serial number 318220-02, 5-1/2" wide x 6-1/2" long flanged infeed, 3" Tri-Clover discharge, 15 HP electric motor gearhead direct drive, 208-230/406/3/60, on mild steel base.
74	MC14	Waukesha model 130 U1 positive displacement pump	Waukesha model 130 U1 positive displacement pump, serial number 1000003100876, 3" Tri-Clover fittings, 5 HP electric motor gearhead direct drive, 1760 RPM, 208-230/460/3/60, on stainless steel base.
75	MC16	Waukesha model 130 positive displacement pump	Waukesha model 130 positive displacement pump, 3" Tri-Clover fittings, 5 HP electric motor gearhead direct drive, 1730 RPM, 208-230/460/3/60, on stainless steel base.
76	MC8	Waukesha model 130 U1 positive displacement pump	Waukesha model 130 U1 positive displacement pump, serial number 1000003035101, 3" Tri-Clover fittings, 3 HP electric motor gearbox direct drive, 1760 RPM, 208-230/460/3/60, on stainless steel base.
77	MC13	Waukesha model 130 positive displacement pump	Waukesha model 130 positive displacement pump, 3" Tri-Clover fittings, 5 HP electric motor drive, 3500 RPM, 208-230/460/3/60, on stainless steel base.

78

	MC4	Waukesha model 130 U1 positive displacement pump	Waukesha model 130 U1 positive displacement pump, serial number 1000002925341, 3" Tri-Clover fittings.
79	7912	Crepaco model 4R stainless steel positive displacement pump	Crepaco model 4R stainless steel positive displacement pump, serial number 8150, 2" threaded connections, stainless steel contact, on a stainless steel base with casters.
80	7913	Crepaco model R6R stainless steel positive displacement pump	Crepaco model R6R stainless steel positive displacement pump, serial number 17488, 3" Tri-Clover connections, 5 HP electric motor gearhead chain drive, 1750 RPM, wired 208-230/3/60, stainless steel construction, on a stainless steel base with casters.
81	7916	Crepaco model R3BS stainless steel positive displacement pump	Crepaco model R3BS stainless steel positive displacement pump, serial number 100354100-0303, 2" Tri-Clover connections, 2 HP electric motor gearhead drive, 1725 RPM, wired 230/460/3/60, stainless steel contact, with a stainless steel base on casters.
82	7917	Crepaco model R3R stainless steel positive displacement pump	Crepaco model R3R stainless steel positive displacement pump, serial number R3R-23802, 1-1/2" threaded connections, 5 HP electric motor gearhead drive, 1750 RPM, wired 460/3/60, stainless steel contact, with a stainless steel base on casters.

83

84	8179	Waukesha Cherry-Burrell stainless steel centrifugal pump	Waukesha Cherry-Burrell stainless steel centrifugal pump, model number C216, 2" Tri-Clover infeed, 1-1/2" Tri-Clover discharge, 3 HP stainless steel electric motor direct drive, 1760 RPM, 230/460/3/60, all stainless steel construction.
85	8180	Waukesha Cherry-Burrell stainless steel centrifugal pump	Waukesha Cherry-Burrell stainless steel centrifugal pump, model number C216, 2" Tri-Clover infeed, 1-1/2" Tri-Clover discharge, 3 HP stainless steel electric motor direct drive, 1760 RPM, 230/460/3/60, all stainless steel construction.
86	8181	Waukesha Cherry-Burrell stainless steel centrifugal pump	Waukesha Cherry-Burrell stainless steel centrifugal pump, model number C216, 2" Tri-Clover infeed, 1-1/2" Tri-Clover discharge, 3 HP stainless steel electric motor direct drive, 1760 RPM, 230/460/3/60, all stainless steel construction.
87	MC10	Ampco stainless steel centrifugal pump	Ampco stainless steel centrifugal pump, model number 30334202, serial number C328/1857, 3" Tri-Clover infeed, 2" Tri-Clover discharge, 5 HP electric motor direct drive, 230/460/3/60, all stainless steel construction.
88	MC15	Stainless steel centrifugal pump	Stainless steel centrifugal pump, 3" Tri-Clover infeed, 2" Tri-Clover discharge, 5 HP electric motor direct drive, 1750 RPM, 208-230/460/3/60, on stainless steel base.

	MC9	Stainless steel centrifugal pump	Stainless steel centrifugal pump, 3" Tri-Clover infeed, 2" Tri-Clover discharge, 7-1/2 HP electric motor direct drive, 1770 RPM, 230/460/3/60, all stainless steel construction, requires motor mount repair.
89	MC6	Gorman-Rupp T Series self-priming centrifugal mild steel pump	Gorman-Rupp T Series self-priming centrifugal mild steel pump, model number T4A60S-B74, serial number 1592655, 4" flanged fittings, 10 HP electric motor belt drive, 1760 RPM, 230/406/3/60, mild steel construction, on mild steel base.
90	8263	Goulds model 3410 mild steel double suction pumps	Goulds model 3410 mild steel double suction pumps, serial number X253C067-2, size 4x6-9, impellor diameter 6.375, rated for 130 GPM, 6" flanged infeed, 4" flanged discharge, 30 HP electric motor direct drive, 3535 RPM, 208-230/460/3/60, mild steel construction, on mild steel base.
91	8272	Cornell 4" non-clog pump	Cornell 4" non-clog pump, 4" flanged fittings, 5 HP electric motor belt drive, 1750 RPM, 230/460/3/60, mild steel construction, on a stainless steel frame.
92	8403	Vortex hopper with water supply tank	Vortex hopper with water supply tank, 24" wide x 36" long 24" deep water supply tank, 1" diameter straight pipe infeed, 4" diameter straight pipe side middle overflow, 2" threaded bottom side discharge to vortex hopper, 18" wide x 36" long x 15" deep vortex hopper, 4" flanged fittings, all stainless steel construction.

93

8406 One lot of 10 stainless steel vortex hoppers One lot of 10 stainless steel vortex hoppers, various sizes.

94

8106 Fam model Mantis slicer Fam model Mantis slicer, serial number 6383, built 2005, currently set on a 12 blade cutting wheel with 4 blades installed, 4" wide x 92" long V-belt assembly, 6" product clearance, with controls, 5 HP electric motor drive, 460/3/60, slicing wheel maximum RPM rated at 2200, all stainless steel construction. (Located at CFM in Lodi, CA)

95

8152 Fam model Mantis slicer Fam model Mantis slicer, serial number 6381, built 2005, currently set on a 12 blade cutting wheel with 4 blades installed, 4" wide x 92" long V-belt assembly, 6" product clearance, with controls, 5 HP electric motor drive, 460/3/60, slicing wheel maximum RPM rated at 2200, all stainless steel construction. (Located at CFM in Lodi, CA)

96

8104 Fam model Mantis slicer Fam model Mantis slicer, serial number 6378, built 2005, currently set on a 12 blade cutting wheel with 4 blades installed, 4" wide x 92" long V-belt assembly, 6" product clearance, with controls, 5 HP electric motor drive, 460/3/60, slicing wheel maximum RPM rated at 2200, all stainless steel construction.

97

8105 Fam model Mantis slicer Fam model Mantis slicer, serial number 6379, built 2005, currently set on a 12 blade cutting wheel with 4 blades installed, 4" wide x 92" long V-belt assembly, 6" product clearance, with controls, 5 HP electric motor drive, 460/3/60, slicing wheel maximum RPM rated at 2200, all stainless steel construction.

98

	8151	Fam model Mantis slicer	Fam model Mantis slicer, serial number 6382, built 2005, currently set on a 12 blade cutting wheel with 4 blades installed, 4" wide x 92" long V-belt assembly, 6" product clearance, with controls, 5 HP electric motor drive, 460/3/60, slicing wheel maximum RPM rated at 2200, all stainless steel construction.
99	8153	Fam model Mantis slicer	Fam model Mantis slicer, serial number 6369, built 2005, 6" product clearance, with controls, 5 HP electric motor drive, 460/3/60, slicing wheel maximum RPM rated at 2200, all stainless steel construction, requires V-belt and cutting head.
100	8143	Urschel model Q (QuantiCut) dicer	Urschel model Q (QuantiCut) dicer, serial number 164, 4 blade impeller, 7.5 HP electric motor belt drive, 1175 RPM, 230/460 volts, 60 HZ, all stainless steel construction, requires all cutting parts, guards, discharge, covers, and controls. (Located at CFM in Lodi, CA)
101	8150	Urschel model Diversa Cut dicer	Urschel model Diversa Cut dicer, serial number 456, 5 HP electric motor drive, 1765 RPM, 230/460/3/60, stainless steel construction, frame only. (Located at CFM in Lodi, CA)
102	8115	Urschel model J dicer	Urschel model J dicer, serial number 510, currently set on 5/8" circular cut x 1/2" cross cut, 10 HP electric motor belt drive, 1760 RPM, 230/460/3/60, all stainless steel construction, requires all guards except discharge chute.
103			

	8239	Urschel model J dicer	Urschel model J dicer, serial number 430, currently set on 1/2" dice, 10" wide x 64" long product infeed belt, 35-1/2" product infeed and discharge height, 10 HP electric motor belt drive, 1740 RPM, wired 230/460/3/60, all stainless steel construction, requires product discharge chute and belt guard.
104	7855	FMC model 300AL peach pitter	FMC model 300AL peach pitter, serial number 10350, built in 2001, 34" wide x 36" long product infeed hopper, 51" product infeed height, 8 lanes with 3-1/2" diameter product pockets, 8" diameter x 36" long product scrubbing brush, 3" clearance under brush, suture and alignment assistance, pitting and splitting knives, common fruit and pit discharge, 22" discharge height, 3 HP electric motor belt drive, wired 480/3/60, all stainless steel construction, spare parts available upon request.
105	8116	Grove Dale Corporation flight feeder and slicer	Grove Dale Corporation flight feeder and slicer, 55" wide x 64" tall flighted bed area, 20 flights, 2" deep flights, each flight is 6-3/4" tall, 32" product infeed height, 56" product discharge height, all stainless steel construction, requires drives, cutting mandrel and guard.
106	8117	Grove Dale Corporation flight feeder and slicer	Grove Dale Corporation flight feeder and slicer, 55" wide x 64" tall flighted bed area, 16 flights, 2" deep flights, each flight is 7-1/2" tall, 32" product infeed height, 52" wide stainless steel gang slicer, 1-1/2" spacing between blades, 52" product discharge height, all stainless steel construction, requires drives.
107	8118	Grove Dale Corporation flight feeder and slicer	Grove Dale Corporation flight feeder and slicer, 55" wide x 64" tall flighted bed area, 16 flights, 2" deep flights, each flight is 7-1/2" tall, 32" product infeed height, 52" wide stainless steel gang slicer, 1-1/2" spacing between blades, 52" product discharge height, all stainless steel construction, requires drives.
108			

	8119	Grove Dale Corporation flight feeder and slicer	Grove Dale Corporation flight feeder and slicer, 55" wide x 64" tall flighted bed area, 16 flights, 2" deep flights, each flight is 7-1/2" tall, 32" product infeed height, 52" wide stainless steel gang slicer, 1-1/2" spacing between blades, 52" product discharge height, all stainless steel construction, requires drives.
109	8164	Grove Dale Corporation flight feeder and slicer	Grove Dale Corporation flight feeder and slicer, 54" wide x 64" tall flighted bed area, 22 flights, 2" deep flights, each flight is 6-3/4" tall, 29" product infeed height, 86" product discharge height into 51-1/2" wide stainless steel gang slicer, 1-3/8" spacing between blades, 52" product discharge height, all stainless steel construction, requires drives.
110	8217	Grove Dale Corporation flight feeder and slicer	Grove Dale Corporation flight feeder and slicer, 55" wide x 72" long flighted bed area, 16 flights, 7-1/2" tall x 2" deep flights, 34" product infeed height, feeds to 53" wide cutting head, 36 blades set on 1-1/2" slice, 58" slicer discharge height, independent electric motor drive for flights and slicer, all stainless steel construction.
111	8218	Grove Dale Corporation flight feeder and slicer	Grove Dale Corporation flight feeder and slicer, 54" wide x 72" long flighted bed area, 12 flights, 7" tall x 2" deep flights, 6 flights at slicer infeed curved for product alignment, 24" product infeed height, feeds to 53" wide cutting head, 35 blades set on 1-5/8" slice, 54" slicer discharge height, all stainless steel construction, requires slicer guard, flight and slicer drives.
112	MC17	Rietz model RP-18-K133 disintegrator	Rietz model RP-18-K133 disintegrator, serial number RP-87001668, 3/8" screen perforation, currently has hammers installed, 40 HP electric motor direct drive, 3530 RPM, 208-230/460/3/60, all stainless steel construction, on stainless steel base.

113

MC44	Custom product slicer	Custom product slicer, slicing mechanism constructed of 4 each 14" diameter blades, 23-1/2" wide x 22" long x 10" deep infeed hopper tapered down to 6-1/2" wide x 6-1/2" long product infeed and discharge, product gravity feed through slicing mechanism and cut in quarters, 4 each electric motor slicer drives, all stainless steel construction.	
114	8133	Stephan model MCH-D40 emulsifier	Stephan model MCH-D40 emulsifier, serial number 3150870, built in 1992, can run up to two milling heads, currently set with one, 10" wide x 12" long x 7" deep hopper feeds to milling feed screw, then into milling heads, 3" Tri-Clover discharge, 75 HP electric motor drive, 3560 RPM, 440/3/60, all stainless steel construction.
115	8134	Stephan model MCH-20K Microcut emulsifier	Stephan model MCH-20K emulsifier, serial number 730.325.01, 18" wide x 21" long x 26" deep hopper infeed with 4-1/2" diameter x 15" long feed screw, currently installed with 2 milling heads, 12" wide x 4" long discharge, 20 HP electric motor drive, 3510 RPM, 230/460/3/60, all stainless steel construction.
116	8071	800 gallon BCast stainless steel steam jacketed kettle	800 gallon BCast stainless steel steam jacketed kettle, model BC-Spec, serial number 22205-1975-19, serial number on jacket 10-2016-13A4, 70" diameter x 66" deep, 100 PSI at 338 degrees Fahrenheit maximum allowable working pressure, -4 degrees Fahrenheit at 100 PSI minimum design metal temperature, 3" diameter straight pipe product discharge, 4 each 2" Tri-Clover center top infeed connections, 2 each 1" threaded steam connections, 316 stainless steel contact, 304 stainless steel construction, requires discharge fitting.
117	8073	400 gallon BCast stainless steel steam jacketed kettle	400 gallon BCast stainless steel steam jacketed kettle, model BCKettle 400, serial number HD-2016-17A9, serial number on jacket 22205-19275-16-14, National Board number 1241, 54" diameter x 52" deep, 100 PSI at 338 degrees Fahrenheit maximum allowable working pressure, -4 degrees Fahrenheit at 100 PSI minimum design metal temperature, 3" straight pipe product discharge, 2 each 2" Tri-Clover center top infeed, 3" Tri-Clover center top product infeed, 1 each 1/2" center top I-line infeed, bracket for mounting agitator, 2 each 1" threaded side connections, 3 each 1" threaded jacket steam connections, stainless steel contact, on mild steel frame, requires discharge fitting.
118	8075	400 gallon BCast stainless steel steam jacketed kettle	400 gallon BCast stainless steel steam jacketed kettle, model BCKettle 400, serial number HD-2017-15A2, National Board number 1515, 54" diameter x 52" deep, 100 PSI at 338 degrees Fahrenheit maximum allowable working pressure, -4 degrees Fahrenheit at 100 PSI minimum design metal temperature, 3" straight pipe product discharge, 2 each 2" Tri-Clover center top infeed, 3" Tri-Clover center top product infeed, 1 each 1/2" center top I-line infeed, bracket for mounting agitator, 2 each 1" threaded side connections, 3 each 1" threaded jacket steam connections, 316 stainless steel contact, 304 stainless steel construction, on mild steel frame, requires discharge fitting.
119			

120	8076	400 gallon BCast stainless steel steam jacketed kettle	400 gallon BCast stainless steel steam jacketed kettle, model BCKettle 400, serial number HD-2017-14A1, National Board number 1512, 54" diameter x 52" deep, 100 PSI at 338 degrees Fahrenheit maximum allowable working pressure, -4 degrees Fahrenheit at 100 PSI minimum design metal temperature, 3" straight pipe product discharge, 2 each 2" Tri-Clover center top infeed, 3" Tri-Clover center top product infeed, 1 each 1/2" center top I-line infeed, bracket for mounting agitator, 2 each 1" threaded side connections, 3 each 1" threaded jacket steam connections, stainless steel contact, on mild steel frame, requires discharge fitting.
	8081	400 gallon BCast stainless steel steam jacketed kettle	400 gallon BCast stainless steel steam jacketed kettle, model BCKettle 400, serial number HD-22305-17A0, National Board number 1514, 54" diameter x 52" deep, 100 PSI at 338 degrees Fahrenheit maximum allowable working pressure, -4 degrees Fahrenheit at 100 PSI minimum design metal temperature, 3" straight pipe product discharge, 2 each 2" Tri-Clover center top infeed, 3" Tri-Clover center top product infeed, 1 each 1/2" center top I-line infeed, bracket for mounting agitator, 2 each 1" threaded side connections, 3 each 1" threaded jacket steam connections, stainless steel contact, on mild steel frame, requires discharge fitting.
121	8135	450 gallon Lee scrape surface jacketed kettle	450 gallon Lee scrape surface jacketed kettle, 53" diameter x 42" deep, 3" Tri-Clover center bottom fitting, 2" threaded jacket infeed, 1" threaded jacket discharge, 3 HP electric motor mixer drive, 1440 RPM, 230/460/3/60, stainless steel contact, mild steel frame.
122	8229	300 gallon Groen stainless steel steam jacketed kettle	300 gallon Groen stainless steel steam jacketed kettle, serial number 16471, 52" diameter x 46" deep, 100 PSI jacket maximum allowable working pressure, 96" product infeed height, 46" product discharge height, 6" straight pipe product discharge, 6" straight pipe side top overflow connection, all stainless steel construction.
123	8198	150 gallon Hamilton stainless steel steam jacketed kettle	150 gallon Hamilton stainless steel steam jacketed kettle, model 1-A, serial number B-7172-2, National Board number 4002, 43" diameter x 35" deep, MAWP 100 PSI at 328 degrees Fahrenheit, 6" flanged center bottom discharge, with level probe, 4" straight pipe upper wall fitting, 2 each 1" threaded jacket fittings, all stainless steel construction.
124	8167	40 cubic foot Stricklin jacketed stainless steel scrape surface paddle mixer	40 cubic foot Stricklin jacketed stainless steel scrape surface paddle mixer, model 147, serial number 47, jacket rated for 100 PSI @ 300 degrees Fahrenheit, 3' wide x 6' long x 24" deep straight wall with additional 16 sloped bottom, paddle mixer with scrappers installed, 4" Cherry Burrell side bottom product discharge, open top, 1" flanged jacket fittings, electric motor belt drive, all stainless steel construction.
125	8168	40 cubic foot Stricklin jacketed stainless steel scrape surface paddle mixer	40 cubic foot Stricklin jacketed stainless steel scrape surface paddle mixer, model 147, serial number 206, jacket rated for 100 PSI @ 300 degrees Fahrenheit, 3' wide x 6' long x 24" deep straight wall with additional 16 sloped bottom, paddle mixer with scrappers installed, 4" Cherry Burrell side bottom product discharge, open top, 1" flanged jacket fittings, electric motor belt drive, all stainless steel construction.
126	8169	40 cubic foot Stricklin jacketed stainless steel scrape surface paddle mixer	40 cubic foot Stricklin jacketed stainless steel scrape surface paddle mixer, model 147, serial number 208, jacket rated for 100 PSI @ 300 degrees Fahrenheit, 3' wide x 6' long x 24" deep straight wall with additional 16 sloped bottom, paddle mixer with scrappers installed, 4" Cherry Burrell side bottom product discharge, open top, 1" flanged jacket fittings, electric motor belt drive, all stainless steel construction.
127	8279	40 cubic foot Stricklin jacketed stainless steel scrape surface paddle mixer	40 cubic foot Stricklin jacketed stainless steel scrape surface paddle mixer, model 147, jacket rated for 100 PSI @ 300 degrees Fahrenheit, 3' wide x 6' long x 24" deep straight wall with additional 16 sloped bottom, paddle mixer with scrappers installed, 4" Cherry-Burrell side bottom product discharge, open top, 1" flanged jacket fittings, electric motor belt drive, all stainless steel construction, requires replacement scrappers.
128			

129	8369	40 cubic foot Stricklin jacketed stainless steel scrape surface paddle mixer	40 cubic foot Stricklin jacketed stainless steel scrape surface paddle mixer, model 147, jacket rated for 100 PSI @ 300 degrees Fahrenheit, 3' wide x 6' long x 24" deep straight wall with additional 16" sloped bottom, paddle mixer with scrappers installed, 4" Cherry-Burrell side bottom product discharge, open top, 1" flanged jacket fittings, 5 HP electric motor belt drive, 1750 RPM, 230/460/3/60, with on/off controls, all stainless steel construction.
130	8215	1000 gallon Cherry-Burrell stainless steel jacketed scrape surface mixing tank	1000 gallon Cherry-Burrell stainless steel jacketed scrape surface mixing tank, 70" diameter x 60" deep, 2-1/2" Tri-Clover bottom side product discharge, 18" diameter manhole with inspection ladder, 2 each 3" Tri-Clover side top product infeeds, 2" Tri-Clover side top product infeed, 1" threaded steam connections, bridge mounted agitator with scrapers, mixer anchored to bottom of tank, threaded manifold with dual spray heads in tank, 19" x 12" inspection platform with handrails, all stainless steel construction.
131	8130	250 gallon Cherry-Burrell Int stainless steel scrape surface insulated tank	250 gallon Cherry-Burrell Int stainless steel scrape surface insulated tank, serial number F141-190-2 M31T04, 3" Tri-Clover product infeed, 2" threaded center bottom discharge with Tri-Clover adaptor, conical bottom, 5 HP electric motor gearhead scrape surface mixer drive, 1730 RPM, 230/460/3/60, all stainless steel construction.
132	8189	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank, model number 500V9MS, serial number B8442A1, National Board number 5655, built in 1993, 55" diameter x 64" deep, MAWP 100 PSI @ 338 degrees Fahrenheit, MDMT 20 degrees Fahrenheit @100 PSI, 4" Tri-Clover center bottom discharge, 5 each 1" threaded jacket fittings, 7-1/2 HP electric motor gearhead mixer drive, 1770 RPM, 230/460/3/60, 2" clearance between scrapers and tank wall, covered top, various product infeeds, all stainless steel construction.
133	8193	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank, model number 500V9MS, serial number C4342A2, National Board number 6947, built 1993, 55" diameter x 64" deep, MAWP 100 PSI @ 338 degrees Fahrenheit, MDMT 20 degrees Fahrenheit @100 PSI, 4" Tri-Clover center bottom discharge, 5 each 1" threaded jacket fittings, 7-1/2 HP electric motor gearhead mixer drive, 1770 RPM, 230/460/3/60, 2" clearance between scrapers and tank wall, covered top, various product infeeds, all stainless steel construction.
134	8194	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank, model number 500V9MS, serial number B8442A1, National Board number 5655, built 1993, 55" diameter x 64" deep, MAWP 100 PSI @ 338 degrees Fahrenheit, MDMT 20 degrees Fahrenheit @100 PSI, 4" Tri-Clover center bottom discharge, 5 each 1" threaded jacket fittings, 1770 RPM, 230/460/3/60, 2" clearance between scrapers and tank wall, covered top, various product infeeds, all stainless steel construction, requires drive.
135	8195	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank, model number 500V9MS, built 1993, 55" diameter x 64" deep, MAWP 100 PSI @ 338 degrees Fahrenheit, MDMT 20 degrees Fahrenheit @100 PSI, 4" Tri-Clover center bottom discharge, 5 each 1" threaded jacket fittings, 7-1/2 HP electric motor gearhead mixer drive, 1770 RPM, 230/460/3/60, 2" clearance between scrapers and tank wall, covered top, various product infeeds, all stainless steel construction.
136	8196	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank, model number 500V9MS, serial number B8442A2, built 1993, 55" diameter x 64" deep, MAWP 100 PSI @ 338 degrees Fahrenheit, MDMT 20 degrees Fahrenheit @100 PSI, 4" Tri-Clover center bottom discharge, 5 each 1" threaded jacket fittings, 7-1/2 HP electric motor gearhead mixer drive, 1770 RPM, 230/460/3/60, 2" clearance between scrapers and tank wall, covered top, various product infeeds, all stainless steel construction.
137	8197	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank, model number 500V9MS, built 1993, 55" diameter x 64" deep, MAWP 100 PSI @ 338 degrees Fahrenheit, MDMT 20 degrees Fahrenheit @100 PSI, 4" Tri-Clover center bottom discharge, 5 each 1" threaded jacket fittings, 7-1/2 HP electric motor gearhead mixer drive, 1770 RPM, 230/460/3/60, 2" clearance between scrapers and tank wall, covered top, various product infeeds, all stainless steel construction.

138	MC43	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank	500 gallon Lee Technologies jacketed scrape surface stainless steel mix tank, model number 500V9MS, serial number 04342A1, built 1997, 55" diameter x 64" deep, MAWP 100 PSI @ 338 degrees Fahrenheit, MDMT 20 degrees Fahrenheit @100 PSI, 4" Tri-Clover center bottom discharge, 5 each 1" threaded jacket fittings, 7-1/2 HP electric motor gearhead mixer drive, 1770 RPM, 230/460/3/60, 2" clearance between scrapers and tank wall, covered top, various product infeeds, all stainless steel construction.
139	8212	450 gallon Stricklin Co. stainless steel jacketed tank	450 gallon Stricklin Co. stainless steel jacketed tank, 48" diameter x 60" deep, with additional 5" cone bottom, 3" Tri-Clover center bottom discharge, 87" product infeed height, 15" product discharge height, 24" tall jacket, 25 square foot heat transfer surface, 150 PSI at 300 degrees Fahrenheit maximum allowable working temperature, various straight pipe and Tri-Clover fittings in removable lid, all stainless steel construction.
140	8214	400 gallon stainless steel tank with mixer	400 gallon stainless steel tank with mixer, 48" diameter x 53" deep, with additional 5" cone bottom, 2" Tri-Clover center bottom discharge, 2" diameter x 36" long steam injection manifold along bottom of tank, various straight pipe and Tri-Clover connections in removable cover, 2 each 1" threaded bottom side connections, 3 blade mixer head, 1-1/2 HP electric mixer motor gearhead drive, 1740 RPM, wired 230/460/3/60, all stainless steel construction.
141	8186	700 gallon stainless steel mixing tank	700 gallon stainless steel mixing tank, 60" diameter x 40" deep with additional 5" cone bottom, 3" Cherry-Burrell center bottom discharge, 18" diameter manhole, various infeeds, Sharpe model SSFGP-100 mixer, serial number 58683-1, 1 HP stainless steel electric motor direct drive, 1720 RPM, 230/460/3/60, all stainless steel construction.
142	8187	700 gallon stainless steel mixing tank	700 gallon stainless steel mixing tank, 60" diameter x 40" deep with additional 5" cone bottom, 3" Cherry-Burrell center bottom discharge, 18" diameter manhole, various infeeds, Sharpe model SSFGP-100 mixer, serial number 59052, 1 HP stainless steel electric motor direct drive, 1720 RPM, 230/460/3/60, all stainless steel construction.
143	8188	700 gallon stainless steel mixing tank	700 gallon stainless steel mixing tank, 60" diameter x 40" deep with additional 5" cone bottom, 3" Cherry-Burrell center bottom discharge, 18" diameter manhole, various infeeds, Sharpe model SSFGP-100 mixer, serial number 58683-2, 1 HP stainless steel electric motor direct drive, 1720 RPM, 230/460/3/60, all stainless steel construction.
144	8211	900 gallon Langsenkamp stainless steel tank	900 gallon Langsenkamp stainless steel tank, model-4, work order number M-5654, 66" diameter x 60" deep, with additional 5" cone bottom, 6" mild steel straight pipe center bottom discharge, 107" product infeed height, 40" product discharge height, 2 each 6" diameter straight pipe side connections, built in 1974, stainless steel and mild steel construction.
145	8213	250 gallon stainless steel tank	250 gallon stainless steel tank, 45" diameter x 36" deep, with additional 19" cone bottom, 6" Tri-Clover discharge with butterfly valve, 2" Tri-Clover side top infeed connection, all stainless steel construction.
146	8227	400 gallon stainless steel tank	400 gallon stainless steel tank, 48" diameter x 60" deep, with 5" cone bottom, 83" product infeed height, 2" Tri-Clover product discharge, 12" product discharge height, all stainless steel construction.
147	8228	400 gallon stainless steel tank	400 gallon stainless steel tank, 44" diameter x 60" deep with additional 5" cone bottom, 75" product infeed height, 2" Tri-Clover product discharge, 10" product discharge height, float ball level control, 4" straight pipe top side overflow connection, 6" straight pipe bottom side discharge, all stainless steel construction.

148	MC2	500 gallon stainless steel tank	500 gallon stainless steel tank, 62" diameter x 40" deep, 17-1/2" diameter manhole, 6" flanged fitting on top of the tank, 2" Tri-Clover top fitting, 2-1/2" threaded top fitting, 2" Tri-Clover center bottom discharge, all stainless steel construction.
	8184	500 gallon stainless steel tank	500 gallon stainless steel tank, 51" diameter x 5' straight wall with additional 6" cone bottom, 4" Tri-Clover center bottom discharge, open top, all stainless steel construction.
149	8185	500 gallon stainless steel tank	500 gallon stainless steel tank, 52" diameter x 5' straight wall with additional 8" cone bottom, 3-1/2" Tri-Clover center bottom discharge, 3 each 6" straight pipe cone bottom discharges, 24" diameter manhole, various infeed fittings, all stainless steel construction, requires 1/2 top cover and manhole cover.
150	8199	550 gallon stainless steel tank	550 gallon stainless steel tank, 48" diameter x 60" tall straight wall with additional 24" deep cone bottom, 6" straight pipe side bottom discharge, discharge is connected to infeed pipe the length of the tank, 4" Tri-Clover upper cone discharge, 26" x 24" catwalk platform with handrails, all stainless steel construction.
151	8100	950 gallon stainless steel tank	950 gallon stainless steel tank, 60" diameter x 6' tall straight wall with additional 28" cone bottom, 6" flanged center bottom discharge with valve, all stainless steel construction.
152	8103	950 gallon stainless steel tank with Lyco parabolic wastewater screen	950 gallon stainless steel tank with Lyco parabolic wastewater screen, 60" diameter x 6' tall straight wall with additional 28" cone bottom, Lyco 36" wide parabolic wastewater screen, 6" flanged center bottom discharge with valve, 6" flanged center side fitting, all stainless steel construction, requires Lyco screen.
153	8158	1000 gallon insulated horizontal mix tank	1000 gallon insulated horizontal mix tank, 52" diameter x 9' long tank, 3 each 19" diameter manholes, 2 each vertical paddle mixers, 2 each 2 HP electric motor gearhead mixer drives, 1740 RPM, 230/460/3/60, 3" Tri-Clover bottom side product discharge, 2 each 3" threaded and 1 each 3" Tri-Clover bottom discharges, 3" Tri-Clover bottom side discharge, all stainless steel construction, requires manhole covers.
154	7811	1000 gallon stainless steel tank	1000 gallon stainless steel tank, 78" diameter x 54" deep straight wall with 12" cone bottom, open top, 120" infeed height, 48-1/2" discharge height, 6" flanged center bottom discharge with knife gate valve, all stainless steel construction.
155	7812	1000 gallon stainless steel tank	1000 gallon stainless steel tank, 78" diameter x 54" deep straight wall with 12" cone bottom, open top, 120" infeed height, 48-1/2" discharge height, 6" flanged center bottom discharge with knife gate valve, all stainless steel construction.

156

157	7813	1000 gallon stainless steel tank	1000 gallon stainless steel tank, 78" diameter x 54" deep straight wall with 12" cone bottom, open top, 120" infeed height, 48-1/2" discharge height, 6" flanged center bottom discharge with knife gate valve, all stainless steel construction, leg requires repair.
	7814	1000 gallon stainless steel tank	1000 gallon stainless steel tank, 78" diameter x 54" deep straight wall with 12" cone bottom, open top, 120" infeed height, 48-1/2" discharge height, 6" flanged center bottom discharge with knife gate valve, all stainless steel construction.
158	7815	1000 gallon stainless steel tank	1000 gallon stainless steel tank, 78" diameter x 54" deep straight wall with 12" cone bottom, open top, 120" infeed height, 48-1/2" discharge height, 6" flanged center bottom discharge with knife gate valve, all stainless steel construction.
159	8225	700 gallon stainless steel rectangular tank	700 gallon stainless steel rectangular tank, 60" wide x 60" long x 48" deep, 93" product infeed height, 2" threaded corner bottom drain with valve, 3 each 6" straight pipe bottom side discharge, 1 each 6" flanged bottom side discharge, all stainless steel construction.
160	8224	900 gallon stainless steel rectangular tank	900 gallon stainless steel rectangular tank, 48" wide x 96" long x 48" deep, 74" product infeed, 2-1/2" Tri-Clover bottom side discharge, 27" discharge height, all stainless steel construction.
161	8230	1800 gallon 2 compartment stainless steel tank	1800 gallon 2 compartment stainless steel tank, 60" wide x 120" long x 60" deep, 1st compartment 60" wide x 71" long x 60" deep, 2 each 5" threaded side bottom drains with valves, 6" straight pipe top side connection, 2nd compartment 60" wide x 41" long x 60" deep, 1 each 5" threaded side bottom drain with valve, 4" straight pipe bottom side connection, 4" straight pipe bottom side connection in each compartment, all stainless steel construction.
162	8107	Stainless steel unsnipped bean remover	Stainless steel unsnipped bean remover, 29" diameter x 52" long drum, all stainless steel construction, requires infeed/takeout shaker for unsnipped beans, one set of trunnions, and drive.
163			

	8114	Stainless steel unsnipped bean remover	Stainless steel unsnipped bean remover, 30" diameter x 52" long drum, all stainless steel construction, requires infeed/takeout shaker for unsnipped beans and drive.
164	8136	Stainless steel unsnipped bean remover	Stainless steel unsnipped bean remover, 30" diameter x 60" long drum, 10" wide x 8' long shaker with 5" tall sides, all stainless steel construction, requires drive and shaker mounting.
165	8183	Stainless steel unsnipped bean remover	Stainless steel unsnipped bean remover, 30" diameter x 60" long drum, all stainless steel construction, requires infeed/takeout shaker for unsnipped beans and drive.
166	8154	Olney model 40LCC cluster cutter	Olney model 40LCC cluster cutter, serial number 17LCC677, 36" wide x 36" long product infeed shaker, 40" wide x 9' tall belt with 7-1/2" long product hooks, 40" wide osculating sickle trimmer, 20" diameter belt cleaning brush, 18" wide x 7' long trash take away conveyor, 2 HP electric motor drives, 1750 RPM, 230/460/3/60, all stainless steel construction, requires product take away conveyor.
167	8155	Olney model 40LCC cluster cutter	Olney model 40LCC cluster cutter, 36" wide x 36" long product infeed shaker, 40" wide x 9' tall belt with 7-1/2" long product hooks, 40" wide osculating sickle trimmer, 20" diameter belt cleaning brush, 18" wide x 7' long trash take away conveyor, 2 HP electric motor drives, 1750 RPM, 230/460/3/60, all stainless steel construction, requires product take away conveyor and trash conveyor belt.
168	8156	Olney model 40LCC cluster cutter	Olney model 40LCC cluster cutter, 36" wide x 36" long product infeed shaker, 40" wide x 9' tall belt with 7-1/2" long product hooks, 40" wide osculating sickle trimmer, 20" diameter belt cleaning brush, 2 HP electric motor drives, 1750 RPM, 230/460/3/60, all stainless steel construction, requires product take away conveyor.
169			

8278	Hughes green bean grader	Hughes green bean grader, model number 050-14433D, serial number 99-19235-04, 24" diameter x 66" long drum, fully adjustable but currently set on a 1" gap, 38" product infeed, 30" product discharge, 2 each 12" wide x 17" long product discharge chutes, electric motor chain drive, all stainless steel construction.
170		
7799	30" diameter x 162" long mild steel rotary lye peeler	30" diameter x 162" long mild steel rotary lye peeler, 3/8" perforations, 17" wide x 36" long infeed hopper, 77" infeed height, 30" diameter auger inside screen, 5 HP electric motor chain drive, 1735 RPM, wired 230/460/3/60, 30" wide x 109" long discharge thermoplastic elevator, 1-1/2" tall cleats spaced every 12", 74" discharge height, 1-1/2 HP electric motor gearhead drive, 1735 RPM, wired 208-220/440/3/60, mild steel and stainless steel construction.
171		
7804	Stainless steel caustic peeler	Stainless steel caustic peeler, 48" wide x 140" long stainless steel mesh conveyor, 39-1/2" wide x 9" tall cleats, every 48", 12" caustic submersion depth, 62-1/2" product infeed height, 82" product discharge height, 24" wide x 14" long exhaust with 19" diameter adapter, 4" straight pipe caustic infeed, belt driven, all stainless steel construction, requires drive.
172		
8145	20 cubic foot stainless steel peel eliminator	20 cubic foot stainless steel peel eliminator, 12" wide x 30" long infeed chute, 4" Tri-Clover top side product infeed, 36" wide x 7' long x 24" deep screen area, 1/4" perforated screen, 7" wide x 4" tall product discharge with adjustable product flow, 29" height product discharge, 4" threaded trash discharge, with product spray heads, 2 each product inspection areas, 3 HP electric motor gearhead chain drive, 1760 RPM, 230/460/3/60, all stainless steel construction.
173		
8165	Odenberg 1000 liter steam peeler vessel	Odenberg 1000 liter steam peeler vessel, National Board number 1107, serial number 16047-2, built 4-2016, Odenberg serial number 101188-2, 42" diameter x 48" deep vessel, MAWP 300 PSI at 425 degrees Fahrenheit, MDMT 0 degrees Fahrenheit at 300 PSI, UW RT4, part of Odenberg system, 5 HP electric motor drive, 1800 RPM, 230/460/3/60, stainless steel frame, mild steel vessel.
174		

175	MC35	Lyc0 model 11900 Hyd War Horse brush washer	Lyc0 model 11900 Hyd War Horse brush washer, serial number P-0914-76015, built 9/14, capable of handling 11 rollers but currently installed with 5 brush rollers and 4 abrasive, 24" wide x 19" long x 29" deep infeed hopper, 24" diameter x 80" long screw with 13-1/2" space between flights, 62" product infeed height, 36" product discharge height, 52" long inner spray bar, 44-1/2" wide x 80-1/2" long x 8" deep waste hopper, all stainless steel construction.
	MC36	Lyc0 model 11900 Hyd War Horse brush washer	Lyc0 model 11900 Hyd War Horse brush washer, serial number P-0914-71025, built 7/14, capable of handling 11 rollers but currently installed with 5 brush rollers and 4 abrasive, 24" wide x 19" long x 29" deep infeed hopper, 24" diameter x 80" long screw with 13-1/2" space between flights, 62" product infeed height, 36" product discharge height, 52" long inner spray bar, 44-1/2" wide x 80-1/2" long x 8" deep waste hopper, all stainless steel construction.
176	MC19	Lyc0 brush scrubber	Lyc0 brush scrubber, capable of handling 8 rollers, 5-1/2" diameter x 69" long rollers, 7 HP electric motor drive , 1185 RPM, 208-230/406/3/60, requires 6 additional brushes and product screw, all stainless steel construction.
177	MC37	Stainless steel brush scrubber	Stainless steel brush scrubber, currently installed with 9 each 6" diameter x 116" long brush scrubbers, capable of handling 10 brushes, 21" wide x 31" long hopper infeed, 31" diameter product area, with 2" diameter x 116" long spray head, 58" product infeed height, 24" dropout discharge height, 3 HP electric motor gearhead chain drive, 1740 RPM, 230/460/3/60, all stainless steel construction.
178	8094	Hughes 48" diameter x 16' long stainless steel hot water rotary blancher	Hughes 48" diameter x 16' long stainless steel hot water rotary blancher, 1/8" perforated screen, 16" diameter infeed and discharge, 8" flanged side bottom inspection/cleanout port, various infeeds and discharge fittings, counter balance lid, 2 HP electric motor gearhead chain drive, all stainless steel construction, requires product infeed and discharge chutes.
179			

180	8091 Idaho Steel hot water perforated screw stainless steel blancher	Idaho Steel hot water perforated screw stainless steel blancher, 72" diameter x 15-1/2' long, 33" wide x 9' tall product infeed, 16" diameter shaft with 26" tall perforated screw, 3/8" perforations, 9' diameter x 24" deep carousel discharge, 24" wide x 16" tall discharge port, product discharges a 89", 4 each 33" wide x 36" long top mounted inspection doors, various Tri-Clover fittings, 4" flanged center bottom discharge with valve, all stainless steel construction.
180	8099 Idaho Steel hot water perforated screw stainless steel blancher	Idaho Steel hot water perforated screw stainless steel blancher, 48" diameter x 18' long, 12" x 24" product infeed, 1/2" diameter screw perforations, 7' diameter carousel discharge, 24" wide x 19" tall product discharge, Iso-Rod screen in discharge chute for dewatering, 3 each 24" wide x 60" long top mounted inspection doors, various Tri-Clover fittings, all stainless steel construction.
181	7816 40" diameter x 178" long stainless steel hot water rotary blancher	40" diameter x 178" long stainless steel hot water rotary blancher, 1/8" wide x 3/8" long slotted perforations, 48" diameter outer shell, 36" wide x 10" long infeed chute, 65" product infeed height, 16-1/2" U-shaped discharge chute, 29" product discharge height, 2" hot water threaded infeed, 5" threaded bottom side connection with plug, 5" flanged bottom side connection with butterfly valve, 2 each 8" diameter clean out, 4 each 1" threaded connections with caps, 2 each 2-1/2" threaded connections with caps, 12" diameter top center exhaust, 10 each 34" wide x 11-1/2" tall access doors, chain driven, stainless contact, mild steel construction, requires drive.
182	7803 A. K. Robins 48" diameter x 12' long stainless steel hot water rotary blancher	A. K. Robins 48" diameter x 12' long stainless steel hot water rotary blancher, 1/8" diameter perforated screen, 18" wide x 15" long infeed hopper, 91" product infeed height, 14-1/2" wide x 42-1/2" long U-shaped discharge chute, 58" product discharge height, 2 each 8" side bottom inspection/cleanout ports, counter balanced lid, various infeed and discharge fittings, 1 each 1" threaded bottom side steam connection with regulator, 1" threaded exhaust connection, 1 each 4" Tri-Clover side bottom connection, 1 each 4" Tri-Clover side bottom connection with threaded adaptor and valve, stainless steel construction, requires drive.
183	8129 42" wide x 30' long stainless steel flooded tank blancher	42" wide x 30' long stainless steel flooded tank blancher, with paddle conveyance, 42" wide x 25' long x 32" deep submersion area, 17" clearance between paddles and bottom of the tank, 2 each 18' long steam lines, 3 each 18" diameter flanged exhaust ports, 42" wide x 6' long incline discharge conveyor to 42" wide x 4' long flat blancher belt conveyor, 45" product infeed height, 57" discharge height, all stainless steel construction.
184	8090 Stainless steel flooded tank blancher	Stainless steel flooded tank blancher, 4' wide x 40' long x 35" deep tank area, 12 each 16" diameter x 44" wide agitators with 8" tall paddles, 2 each 2" diameter x approximately 30' long perforated steam pipe in basin of vessel, various tank fittings, 42" wide x 9' long discharge conveyor, approximate 6' dump height, 2 each 8" diameter steam exhaust ports, 5 HP electric motor gearhead chain shared agitators drive, 1745 RPM, 208-230/460/3/60, all stainless steel construction, requires conveyor belt, drive, and tail pulley.
185		

	8138	Rossi Contherm 4 barrel heat exchanger	Rossi Contherm 4 barrel heat exchanger, includes model number 0302071, serial numbers 973.1 - 973.4, 4 each approximately 14" diameter x 9-1/2' long swept surface tubes, approximately 136 square feet of total surface area, 3" product and heating mechanism fittings, 1/2" steam lines in addition to the main heating piping, shell rated at 72.5 psi DP, 318 degrees Fahrenheit DT, 108.75 psi TP, 176 degree Fahrenheit MDMT, tube rate at 213 psi DP, 203 degrees Fahrenheit DT, 312.4 psi TP, 176 degrees Fahrenheit MDMT, 15 HP electric motor drives, 1750 RPM, 230/460/3/60, all stainless steel construction, requires 2 each drive motors.
186	8159	Alfa-Laval Contherm 3 barrel swept surface heat exchanger	Alfa-Laval Contherm 3 barrel swept surface heat exchanger, model 6 x 9, barrel one: National Board number 1437, serial number HC11370SCNH, built in 2014, product rating of MAWP 300 PSI @338 degrees Fahrenheit, MDMT -30 degrees Fahrenheit @300 PSI, media chamber rating MAWP 0 PSI @338 degrees Fahrenheit, MDMT -30 degrees Fahrenheit @ 250 PSI, 2" Tri-Clover fittings, 10 HP electric motor drive, 1180 RPM, 230/460/3/60, barrel two: product rating of MAWP 300 PSI @338 degrees Fahrenheit, MDMT -30 degrees Fahrenheit @300 PSI, media chamber rating MAWP 0 PSI @338 degrees Fahrenheit, MDMT -30 degrees Fahrenheit @ 250 PSI, 2" Tri-Clover fittings, 10 HP electric motor drive, 1180 RPM, 230/460/3/60, barrel three: National Board number 417, serial number HC9367SCNH, built in 2005, product rating of MAWP 300 PSI @338 degrees Fahrenheit, MDMT -30 degrees Fahrenheit @300 PSI, media chamber rating MAWP 0 PSI @338 degrees Fahrenheit, MDMT -30degrees Fahrenheit @ 250 PSI, 2" Tri-Clover fittings, 10 HP electric motor drive, 1180 RPM, 230/460/3/60, all stainless steel construction.
187	8262	American Heat Reclaiming spiral heat exchanger	American Heat Reclaiming spiral heat exchanger, National Board number 13431, manufacturer number 17651, built 1986, 70 square feet surface area, maximum allowable working pressure 50 PSI at -20 to 200 degrees Fahrenheit, head material SA-516-70, shell material SA-240-304, mild steel construction.
188	8236	Solbern model PTF tumble filler	Solbern model PTF tumble filler, fully adjustable but currently set on 300 can size, product gates with 1/2" diameter stainless steel fingers every 1-1/4", 23" wide x 35-1/2" long product feed pan, standard Solbern feed chain, non-standard controls, 1 HP electric drum motor, 1740 RPM, wired 208-230/460/3/60, 2 HP electric conveyor motor, 1720 RPM, all stainless steel construction, requires drum covers, 2 each product gates, and shaker motor.
189	8238	Solbern model PTF tumble filler	Solbern model PTF tumble filler, serial number 1247, fully adjustable but currently set on 603 x 700 can size, 35" wide x 22" long solid product pan, cascading fill zone, Volta conveyor cable, 38" container infeed and discharge height, 23" wide x 35-1/2" long product topping table, 20 stationary product gates with 20 each 1/4" diameter x 1-1/3" long product bars spaced every 1-1/4", 2 HP electric motor gearhead drive, 1740 RPM, wired 230/460/3/60, 1-1/2 HP electric motor drum drive, 1720 RPM, wired 230/460/3/60, all stainless steel construction, requires drum covers, infeed chute, 2 each product gates, and shaker drive.

191	8241	Solbern model PTF tumble filler	Solbern model PTF tumble filler, fully adjustable but currently set on 300 diameter can size, 12" wide x 29" long solid product pan, cascading fill zone, Volta conveyor cable, 32" container infeed and discharge height, currently set on 20 stationary product gates with 2" diameter x 24" long product bars, electric motor shaker drive, 2 HP electric motor gearhead conveyor drive, electric motor drum drive, all stainless steel construction, requires drum covers, product infeed chute, and product topping tray.
	8242	Solbern model FTF tumble filler	Solbern model FTF tumble filler, serial number 106766, fully adjustable but currently set on 311 diameter can size, 23" wide x 33" long solid product pan, cascading fill zone, Volta conveyor cable, 32" container infeed and discharge height, 23" wide x 33" long product topping table, 20 stationary product gates with 1/4" diameter x 1-3/4" long product bars, 2 HP electric motor gearhead conveyor drive, 1750 RPM, wired 208-230/460/3/60, 2 HP electric motor drum drive, 1750 RPM, wired 208-230/460/3/60, all stainless steel construction, requires drum covers and shaker drive.
192	8256	Solbern model FTF tumble filler	Solbern model FTF tumble filler, fully adjustable but currently set on 300 can size, 18" wide x 31" long solid product pan, cascading fill zone, Volta conveyor cable, 30" container infeed and discharge height, 18" wide x 31" long product topping table, 11" wide x 6-1/2" tall product infeed chute, 20 stationary product gates with 1/4" diameter x 1-3/4" long product bars, 2 HP electric conveyor motor gearhead drive, 1750 RPM, wired 208-230/460/3/60, 2 HP electric drum motor drive, 1750 RPM, wired 208-230/460/3/60, 1 HP electric shaker motor gearhead belt drive, 1745 RPM, wired 208-230/460/3/60, all stainless steel construction, requires drum covers.
193	8266	Solbern model FTF tumble filler	Solbern model FTF tumble filler, serial number 26904, frame only.
194	8267	Solbern model FTF tumble filler	Solbern model FTF tumble filler, serial number 3244, fully adjustable but currently set on 603 x 700 can size, 22" wide x 35" long product feed pan, 2 HP electric motor gearhead drum drive, 1740 RPM, 208-230/460,3/60, 2 HP electric motor gearhead conveyor drive, 1740 RPM, 208-230/460,3/60, requires feed chain, drum covers, infeed chute, one motor drive and one set of product buckets.
195	8268	Stainless steel overflow briner	Stainless steel overflow briner, fully adjustable but currently set on a 4-1/2" diameter container, 5' long product fill zone, 12' long volta cable belt, 23" wide x 83" long x 15" deep recirculation tank with 2" diameter x 70" long dual pass tubular heat exchanger, 3" Tri-Clover center bottom recirculation tank discharge with ball valve and 2 each 2" Tri-Clover fitting, Waukesha model 130 positive displacement pump, 3" Tri-Clover fittings, 5 HP electric motor direct drive, 1735 RPM, 230/460/3/60, 2 HP electric motor conveyor drive, 1755 RPM, 230/460/3/60, all stainless steel construction.
196			

	8269	Stainless steel overflow briner	Stainless steel overflow briner, fully adjustable but currently set on a 4-1/2" diameter container, 5' long product fill zone, 12' long volta cable belt, 23" wide x 83" long x 15" deep recirculation tank with 2" diameter x 70" long dual pass tubular heat exchanger, 3" Tri-Clover center bottom recirculation tank discharge with ball valve and 2 each 2" Tri-Clover fitting, Waukesha model 130-U1 positive displacement pump, serial number 1000002956010, 3" Tri-Clover fittings, 5 HP electric motor direct drive, 1735 RPM, 230/460/3/60, 2 HP electric motor conveyor drive, 1755 RPM, 230/460/3/60, all stainless steel construction.
197	8270	Stainless steel overflow briner	Stainless steel overflow briner, fully adjustable but currently set on a 4-1/2" diameter container, 5' long product fill zone, 12' long volta cable belt, 23" wide x 83" long x 15" deep recirculation tank with 2" diameter x 70" long dual pass tubular heat exchanger, 3" Tri-Clover center bottom recirculation tank discharge with ball valve and 2 each 2" Tri-Clover fitting, Waukesha model 130-U1 positive displacement pump, serial number 1000003001230, 3" Tri-Clover fittings, 5 HP electric motor direct drive, 1735 RPM, 230/460/3/60, 2 HP electric motor conveyor drive, 1755 RPM, 230/460/3/60, all stainless steel construction.
198	8407	Stainless steel overflow briner	Stainless steel overflow briner, fully adjustable but currently set on a 4-1/2" diameter container, 50" long product fill zone, 12' long volta cable belt, 23" wide x 83" long x 15" deep recirculation tank with 2" diameter x 70" long dual pass tubular heat exchanger, 3" Tri-Clover center bottom recirculation tank discharge with ball valve and 2 each 2" Tri-Clover fitting, all stainless steel construction.
199	8408	Stainless steel overflow briner	Stainless steel overflow briner, fully adjustable but currently set on a 4-1/2" diameter container, 5' long product fill zone, 12' long volta cable belt, 23" wide x 83" long x 15" deep recirculation tank with 2" diameter x 70" long dual pass tubular heat exchanger, 3" Tri-Clover center bottom recirculation tank discharge and 3" Tri-Clover fitting, 5 HP electric motor direct drive, 1735 RPM, 230/460/3/60, 2 HP electric motor conveyor drive, 1755 RPM, 230/460/3/60, all stainless steel construction.
200	MC45	Zacmi 60 pocket volumetric pocket filler	Zacmi 60 pocket volumetric pocket filler, model number 0233-T-060/1269, built in 2004, currently set on 300 can size, star to counter clockwise rotation to star, upper pocket is 2-1/2" diameter x 2-1/2" deep, lower pocket is 2-3/4" diameter x 3-1/2" deep, 77" diameter product bowl, 3-1/2 HP electric motor drive, requires table top infeed and discharge conveyor and guide rails.
201	8163	Zacmi 40 station volumetric pocket filler	Zacmi 40 station volumetric pocket filler, model number 0201-T-040-531, currently set on 300 can size, counter clockwise rotation, 2-1/4" diameter x 3" deep upper pockets, 2-3/4" diameter x 2" deep lower pockets, level sensor and pocket rinser, 1-1/4 HP electric motor gearhead drive, 1750 RPM, 230/460/3/60, all stainless steel construction, requires one set of upper and lower pockets, infeed/discharge conveyor, and timing worm. (Located at CFM in Lodi, CA)
202			

	8147	Zacmi 40 station rotary volumetric pocket filler	Zacmi 40 station rotary volumetric pocket filler, currently set on 300 x 407 can size, table top conveyor to star infeed, clockwise rotation, star to table top conveyor discharge, 2-3/8" diameter x 2" deep upper pockets, 2-1/2" diameter x 2-3/8" deep lower pockets, 57" diameter bowl, 42" long product drop zone, 1-1/4 HP electric motor gearhead filler drive, 1750 RPM, 230/460/3/60, all stainless steel construction, requires table top belt and drive, infeed and discharge star.
203	8146	Zacmi 20 station volumetric pocket filler	Zacmi 20 station volumetric pocket filler, model number 0201-T-020/526, built 1994, currently set on 603 x 700 can size, table top conveyor to star infeed, counter clockwise rotation, star to table top conveyor discharge, 5" diameter x 5-1/8" deep upper pockets, 5-1/4" diameter x 5-1/4" deep lower pockets, 60" diameter bowl, 4' product drop zone, manual bowl adjustment, all stainless steel construction, requires 2 each upper pockets, table top belt, lower end of filler, filler and conveyor drives. (Located at CFM in Lodi, CA)
204	8149	FMC 15 station pea and bean filler	FMC 15 station pea and bean filler, model number 15STA, serial number HM-838, 401 can size modified to run 300 can size, straight line infeed to timing worm to clockwise rotation, 3" diameter x 1-1/2" deep upper pocket, 3-1/4" diameter x 1" tall lower pocket with 2-1/4" diameter discharge, 2 HP electric motor gearhead drive, 1755 RPM, 230/460/3/60, all stainless steel construction.
205	8355	FMC model 12G granular filler	FMC model 12G granular filler, 3" wide table top infeed to timing worm to counterclockwise rotation, 4-3/8" diameter x 3" deep upper pockets, 4-7/8" diameter x 3-5/8" deep lower pockets, 2 HP electric motor gearhead drive, 1740 RPM, 230/460/3/60, requires lower pockets, infeed star, can guides, discharge, and motor repair.
206	8277	Nalbach model OHF 43 station pocket filler	Nalbach model OHF 43 station pocket filler, serial number 18563, counter clockwise rotation, 46" long drop zone, tangential discharge, 2-1/8" diameter x 3" deep pockets, manual bowl adjustment, 1/2 HP electric motor drive, 1725 RPM, 230/460/3/60, stainless steel contact, mild steel frame.
207	7315	16 station volumetric pocket filler	16 station volumetric pocket filler, upper pockets 3" diameter x 4" deep, lower pockets 3" diameter x 1-1/2" deep, with electric motor drive, all stainless steel construction.
208	8144	FMC model C210 21 station piston filler	FMC model C210 21 station piston filler, currently set on 300 x 407 can size, 3-1/4" table top conveyor to timing worm to infeed star, counterclockwise rotation, tangential discharge, 3-1/2" diameter x 3" deep pistons, 1-1/2" diameter plunger ports, 2 HP electric motor gearhead drive, 1750 RPM, 208-230/460/3/60, with clamp on mixer, on stainless steel base. (Located at CFM in Lodi, CA)
209			

	MC46	FMC M&S 20 pocket rotary piston filler	FMC M&S 20 pocket rotary piston filler, currently set on 300 can size, conveyor to worm to star infeed, counter-clockwise rotation, tangential discharge, 34" diameter x 18" deep bowl, 1-1/2" diameter pistons, 1-3/8" diameter valves with 1-1/4" wide x 3" long ports, mild steel base.
210	MC3	Rostego six station rotary piston filler	Rostego six station rotary piston filler, currently set on 603 x 700 can size, table top to timing worm to star infeed, counter clockwise rotation, tangential discharge, 6" diameter pistons with 8" stroke, 1-5/8" wide x 2-7/8" long valve ports, 16" diameter x 40" deep product bowl, stainless steel contact, mild steel base, requires drive.
211	7309	Zilli & Bellini 40 station piston filler	Zilli & Bellini 40 station piston filler, 60" diameter x 16" deep raised center product bowl, 2-1/4" diameter bowl port, 2" wide x 1-3/4" tall product port, 2" diameter x 30" deep piston and 2-1/2" diameter x 31-1/2" piston on each station, with spray bar to clean product discharge, with bowl product paddle mixer, pneumatic bowl adjustment, 2 each 4" diameter product infeeds, all stainless steel construction, requires infeed, discharge, pistons, and valves.
211A	7311	FMC model 70 PVS eighteen station pre-vacuuminizing syruper	FMC model 70 PVS eighteen station pre-vacuuminizing syruper, serial number 7910-94-62, set on 307 x 409 can size, timing screw to infeed star, counterclockwise rotation, star discharge, no can no fill, with vacuum trap, stainless steel contact, mild steel frame.
212	8148	Angelus model 40P-DF four head can closing machine	Angelus model 40P-DF four head can closing machine, serial number 6777867, currently set on 401 x 411 can size, straight line infeed, automatic cover feed, requires lifting pads and drives. (Located at CFM in Lodi, CA)
213	8137	Angelus model 40P four head can closing machine	Angelus model 40P four head can closing machine, serial number 12014390, currently set on 303 can size, disc infeed to product topper, with cover feed, risen lifters, mild steel construction, requires drive. (Located at CFM in Lodi, CA)
214	8083	Dundon Iron Works single door horizontal mild steel retort	Dundon Iron Works single door horizontal mild steel retort, National Board number 4010, 60" diameter x 31'-0" long, 9 each 36" wide x 40" long x 33-1/2" deep baskets, MAWP 30 PSI at 450 degrees Fahrenheit, MDMT -20 degrees Fahrenheit at 30 PSI, certified in 2013, bottom steam sparge, mild steel construction.
215			

8084	Reid Boiler Works single door horizontal mild steel retort	Reid Boiler Works single door horizontal mild steel retort, National Board number 671, 60" diameter x 31'-0" long, 9 each 36" wide x 40" long x 33-1/2" deep baskets, MAWP 30 PSI at 450 degrees Fahrenheit, MDMT -20 degrees Fahrenheit at 30 PSI, certified in 2013, bottom steam sparge, mild steel construction.
216		
8085	Reid Boiler Works Single door horizontal mild steel retort	Reid Boiler Works Single door horizontal mild steel retort, 60" diameter x 31'-0" long, 9 each 36" wide x 40" long x 33-1/2" deep baskets, MAWP 30 PSI at 450 degrees Fahrenheit, MDMT -20 degrees Fahrenheit at 30 PSI, certified in 2013, bottom steam sparge, mild steel construction.
217		
8086	Reid Boiler Works single door horizontal mild steel retort	Reid Boiler Works single door horizontal mild steel retort, National Board number 667, 60" diameter x 31'-0" long, 9 each 36" wide x 40" long x 33-1/2" deep baskets, MAWP 30 PSI at 450 degrees Fahrenheit, MDMT -20 degrees Fahrenheit at 30 PSI, certified in 2013, bottom steam sparge, mild steel construction.
218		
8087	Dundon Iron Works single door horizontal mild steel retort	Dundon Iron Works single door horizontal mild steel retort, National Board number 4010, 60" diameter x 31'-0" long, MAWP 30 PSI at 450 degrees Fahrenheit, MDMT -20 degrees Fahrenheit at 30 PSI, certified in 2013, bottom steam sparge, mild steel construction, requires baskets.
219		
8088	Dundon Iron Works single door horizontal mild steel retort	Dundon Iron Works single door horizontal mild steel retort, National Board number 4010, 60" diameter x 31'-0" long, 1 each 36" wide x 40" long x 33-1/2" deep baskets, MAWP 30 PSI at 450 degrees Fahrenheit, MDMT -20 degrees Fahrenheit at 30 PSI, certified in 2013, bottom steam sparge, mild steel construction, requires additional baskets.
220		
8089	House Industries Incorporated model HCD stainless steel aerator	House Industries Incorporated model HCD stainless steel aerator, serial number 18601, 3' diameter x 15-1/2' long aerator with 6" wide x 12" long angled paddles, 30" diameter x 15' long floats, 30 HP electric motor chain drive, 1765 RPM, 230/460/3/60, all stainless steel construction.
221		
8200	House Industries Incorporated model HCD stainless steel aerator	House Industries Incorporated model HCD stainless steel aerator, serial number 18606, 3' diameter x 15-1/2' long aerator with 6" wide x 12" long angled paddles, 30" diameter x 15' long floats, 30 HP electric motor chain drive, 1765 RPM, 230/460/3/60, all stainless steel construction.
222		
8201	House Industries Incorporated model HCD stainless steel aerator	House Industries Incorporated model HCD stainless steel aerator, serial number 18604, 3' diameter x 15-1/2' long aerator with 6" wide x 12" long angled paddles, 30" diameter x 15' long floats, 30 HP electric motor chain drive, 1765 RPM, 230/460/3/60, all stainless steel construction.
223		
8202	House Industries Incorporated model HCD stainless steel aerator	House Industries Incorporated model HCD stainless steel aerator, serial number 18608, 3' diameter x 15-1/2' long aerator with 6" wide x 12" long angled paddles, 30" diameter x 15' long floats, 30 HP electric motor chain drive, 1765 RPM, 230/460/3/60, all stainless steel construction.
224		
8203	House Industries Incorporated model HCD stainless steel aerator	House Industries Incorporated model HCD stainless steel aerator, serial number 18603, 3' diameter x 15-1/2' long aerator with 6" wide x 12" long angled paddles, 30" diameter x 15' long floats, 30 HP electric motor chain drive, 1765 RPM, 230/460/3/60, all stainless steel construction.
225		

226	8204	House Industries Incorporated model HCD stainless steel aerator	House Industries Incorporated model HCD stainless steel aerator, serial number 18599, 3' diameter x 15-1/2' long aerator with 6" wide x 12" long angled paddles, 30" diameter x 15' long floats, 30 HP electric motor chain drive, 1765 RPM, 230/460/3/60, all stainless steel construction.
227	8205	House Industries Incorporated model HCD stainless steel aerator	House Industries Incorporated model HCD stainless steel aerator, serial number 18605, 3' diameter x 15-1/2' long aerator with 6" wide x 12" long angled paddles, 30" diameter x 15' long floats, 30 HP electric motor chain drive, 1765 RPM, 230/460/3/60, all stainless steel construction.
228	8206	House Industries Incorporated model HCD stainless steel aerator	House Industries Incorporated model HCD stainless steel aerator, serial number 18598, 3' diameter x 15-1/2' long aerator with 6" wide x 12" long angled paddles, 30" diameter x 15' long floats, 30 HP electric motor chain drive, 1765 RPM, 230/460/3/60, all stainless steel construction.
229	8207	House Industries Incorporated model HCD stainless steel aerator	House Industries Incorporated model HCD stainless steel aerator, serial number 18600, 3' diameter x 15-1/2' long aerator with 6" wide x 12" long angled paddles, 30" diameter x 15' long floats, 30 HP electric motor chain drive, 1765 RPM, 230/460/3/60, all stainless steel construction.
230	8208	House Industries Incorporated model HCD stainless steel aerator	House Industries Incorporated model HCD stainless steel aerator, serial number 18602, 3' diameter x 15-1/2' long aerator with 6" wide x 12" long angled paddles, 30" diameter x 15' long floats, 30 HP electric motor chain drive, 1765 RPM, 230/460/3/60, all stainless steel construction.
231	8209	House Industries Incorporated model HCD stainless steel aerator	House Industries Incorporated model HCD stainless steel aerator, serial number 18607, 3' diameter x 15-1/2' long aerator with 6" wide x 12" long angled paddles, 30" diameter x 15' long floats, 30 HP electric motor chain drive, 1765 RPM, 230/460/3/60, all stainless steel construction.
	MC31	18" wide Hycor stainless steel hydrasieve	18" wide Hycor stainless steel hydrasieve, model number H8-18, serial number H0012709Z, 18" wide x 36" long, 0.040" screen gap, 4" threaded infeed, 6" flanged discharge with 2" threaded adaptor, all stainless steel construction.
232	8232	36" wide Lyco hydrasieve	36" wide Lyco hydrasieve, 36" wide x 62" tall, 1/8" Iso-Rod screen, 6" flanged bottom side discharge, 2" Tri-Clover middle rear discharge, all stainless steel construction.
233	8233	36" wide Lyco hydrasieve	36" wide Lyco hydrasieve, 36" wide x 62" tall, serial number STS020019687-3, 1/16" Iso-Rod screen, 6" flanged bottom side discharge, with butterfly valve, 2" straight pipe middle rear discharge, all stainless steel construction.
234			

	8248	36" wide Lyco hydrasieve	36" wide Lyco hydrasieve, 36" wide x 32" tall screen, 1/16" Iso-Rod screen, 6" flanged bottom side discharge, 2" Tri-Clover side connection, 1" threaded side connection, 12" wide x 36" long x 20" deep water overflow basin, 2" Tri-Clover bottom rear discharge, all stainless steel construction.
235	8253	36" wide Lyco hydrasieve	36" wide Lyco hydrasieve, model STS020019687-1, 36" wide x 28" tall screen, 1/16" Iso-Rod screen, 6" straight pipe bottom side discharge, 12" wide x 36" long x 27" deep water overflow basin, 2" Tri-Clover bottom rear discharge, all stainless steel construction.
236	8254	36" wide Lyco hydrasieve	36" wide Lyco hydrasieve, model STS020019687-1, 36" wide x 28" tall screen, 1/16" Iso-Rod screen, 6" straight pipe bottom side discharge, 12" wide x 36" long x 27" deep water overflow basin, 2" Tri-Clover bottom rear discharge, all stainless steel construction.
237	8255	36" wide Lyco hydrasieve	36" wide Lyco hydrasieve, model STS, serial number STS020019687-6, 36" wide x 28" tall screen, 0.060" screen spacing, 6" straight pipe bottom side discharge, 12" wide x 36" long x 27" deep water overflow basin, 2" Tri-Clover bottom rear discharge, all stainless steel construction.
238	8243	36" wide Lyco hydrasieve	36" wide Lyco hydrasieve, 36" wide x 32" tall screen, 1/16" Iso-Rod screen, 6" threaded bottom rear discharge with ball valve, 4" threaded top side connection, 36" wide x 13" long x 15" deep product discharge chute, all stainless steel construction, requires frame.
239	8110	Lyco 36" wide hydrasieve	Lyco 36" wide stainless steel hydrasieve, flanged fittings, all stainless steel construction, requires screen.
240			

241	MC18	32" wide Lyco hydrasieve	32" wide Lyco hydrasieve, 32" wide x 28" tall, 1/8" Iso-Rod screen, 4" threaded discharge with valve, all stainless steel construction, on stand.
242	MC30	60" wide stainless steel hydrosieve	60" wide stainless steel hydrosieve, 60" wide x 28" tall screen, 1/8" perforations, 13" wide x 26" long x 26" deep catch basin, 4" threaded discharge, all stainless steel construction.
243	MC42	36" wide stainless steel hydrosieve	36" wide stainless steel hydrosieve, 36" wide x 28" tall screen, 1/8" perforations, 3" threaded infeed, 6" straight pipe waste discharge, all stainless steel construction.
244	8111	48" wide stainless steel hydrasieve	48" wide stainless steel hydrasieve, 48" wide x 28" tall screen, 1/8" perforated screen, 6" straight pipe fitting, all stainless steel construction.
245	8112	48" wide stainless steel hydrasieve	48" wide stainless steel hydrasieve, 48" wide x 28" tall screen, 1/8" Iso-Rod screen, 6" straight pipe fitting, all stainless steel construction, screen requires mounting.
246	8235	60" wide Lyco hydrasieve	60" wide Lyco hydrasieve, 60" wide x 28" tall screen, 1/8" Iso-Rod screen, 6" straight pipe bottom side discharge, 60" wide x 12" wide x 32" deep overflow catch basin, 4" overflow discharge with valve, all stainless steel construction.

8237	60" wide Lyco hydrasieve	60" wide Lyco hydrasieve, 60" wide x 28" tall screen, 1/8" Iso-Rod screen, 6" straight pipe bottom side discharge, 60" wide x 12" wide x 32" deep overflow catch basin, 4" overflow discharge with valve, all stainless steel construction.
247		
8411	36" wide stainless steel hydrosieve	36" wide stainless steel hydrosieve, 36" wide x 28" tall screen, 1/8" perforations, 3" threaded infeed, 4" straight pipe infeed, 6" straight pipe waste discharge, all stainless steel construction.
248		
8113	48" wide stainless steel hydrasieve	48" wide stainless steel hydrasieve, 48" wide x 28" tall screen, 1/8" perforated screen, 4" and 6" fittings, all stainless steel construction.
249		
7318	48" wide stainless steel hydrasieve	48" wide stainless steel hydrasieve, 56" long screen, 1/16" screen gap, 3-1/2" and 4-1/2" straight pipe infeed openings, 5" and 11" straight pipe discharges, all stainless steel construction.
250		
8131	Burt roll through labeler	Burt roll through labeler, left to right feed, with controls, on casters, requires label bed and cold glue pot.
251		

MC22	Mild steel pallet inverter	Mild steel pallet inverter, opened dimensions are 50" wide x 69" tall, clamped dimensions are 50" wide x 39 1/2" tall, manual controls, 3 HP powerpack, 1725 RPM, 208-230-460/3/60, 8" wide x 22-1/2" long x 11" deep hydraulic powerpack reservoir, with forklift guides, mild steel construction.
252		
8161	Key Optyx color sorter	Key Optyx color sorter, 23-1/2" wide x 7' long infeed conveyor with product separating carriage, 1/3 HP electric motor drive, 1720 RPM, 230/460/3/60, 2 each cameras, pneumatic air knife rejection, rigidized stainless steel diverting pan, all stainless steel construction requires CPU.
253		
8356	Fortress metal detector	Fortress metal detector, 30" wide x 5" tall aperture, 28" wide x 84" long rubber belt conveyor, 1/2 HP electric motor belt drive, 1755 RPM, 230/460/3/60, with pneumatically controlled reject, all stainless steel construction.
255		
8166	Quincy model QT-10 air compressor	Quincy model QT-10 air compressor, model number QT10VT1000033, serial number 20031023-0008, National Board number 224910, built 2003, 115 gallon tank, MAWP 200 PSI @ 650 degrees Fahrenheit, MDMT -20 degrees Fahrenheit @ 200 PSI, 10 HP electric motor belt drive, 1760 RPM, 230/460/3/60, start stop controls, mild steel construction.
256		
MC1	Quincy model QT-10 air compressor	Quincy model QT-10 air compressor, model number QT10VT1000033, serial number 20040527-0003, National Board number 305942, built 2004, 115 gallon tank, MAWP 200 PSI @ 650 degrees Fahrenheit, MDMT -20 degrees Fahrenheit @ 200 PSI, 10 HP electric motor belt drive, 1760 RPM, 230/460/3/60, start stop controls, mild steel construction.
257		

258	MC21	Hankison International model PR400-460 compressed air dryer	Hankison International model PR400-460 compressed air dryer, serial number 0363-2T-9610-84N, 2" threaded fittings, MAWP 200 PSIG, maximum inlet temperature 120 degrees Fahrenheit, refrigerant type R-22, 2 HP electric motor drive, 460/3/60, mild steel construction.
259	MC20	Hot water production skid	Hot water production skid, Sondex model S7-IG-44 plate heat exchanger, serial number 21483, 22 each 4" wide x 18" tall plates, MAWP 150 PSI at 284 degrees Fahrenheit, MDMT 32 degrees Fahrenheit at 150 PSI, American Steam Incorporated vessel, repairs by Mid-South Steam Boiler and Eng Company Incorporated, 100 gallon vessel, 24" diameter x 54" tall, MAWP 250 PSI at 450 Fahrenheit, National Board R number R-2223, on mild steel base.
260	MC39	Amiad self cleaning filter	Amiad self cleaning filter, model SAF-4500, serial number 03-10-84, category number 03-2061-1110-3500, 6" flanged fittings, 1/4" screen perforations, 2" diameter exhaust valve, Maximum working pressure of 150 PSI, maximum working temperature of 176 degrees Fahrenheit, 1/3 HP electric motor direct drive, 1610 RPM, 260/440/3/60, mild steel construction.
261	MC40	Amiad self cleaning filter	Amiad self cleaning filter, model SAF-4500, category number 03-2061-1110-3500, 6" flanged fittings, 1/4" screen perforations, 2" diameter exhaust valve, Maximum working pressure of 150 PSI, maximum working temperature of 176 degrees Fahrenheit, 1/3 HP electric motor direct drive, 1610 RPM, 260/440/3/60, mild steel construction.
262	MC41	Amiad self cleaning filter	Amiad self cleaning filter, model SAF-4500, category number 03-2061-1110-3500, 6" flanged fittings, 1/4" screen perforations, 2" diameter exhaust valve, Maximum working pressure of 150 PSI, maximum working temperature of 176 degrees Fahrenheit, 1/3 HP electric motor direct drive, 1610 RPM, 260/440/3/60, mild steel construction.

	8240	Phelps Industries 80 HP hydraulic powerpack	Phelps Industries 80 HP hydraulic powerpack, model number S-40-600RP, serial number 472-41, 600 gallon reservoir, 60" wide x 72" long x 34" deep, manual controls, 2 each hydraulic pumps, 40 HP electric motor direct drives, 1765 RPM, wired 230/460/3/60, all mild steel construction.
263	8157	Tower Tech Inc cooling tower	Tower Tech Inc Cooling tower, model number TTMT.144.319, serial number 1205.49.01.01.01, built in 1-17-87, 144" wide x 140" long x 137" tall tower, 8" flanged top side fitting, 21" wide x 14" tall bottom side flanged fitting, mild steel construction.
264	8271	Coenco natural gas heater and fan	Coenco natural gas heater and fan, serial number 5214, with adjustable temperature controls, electric motor drive, mild steel construction.
265	7207	Hannay mild steel hose reel	Hannay mild steel hose reel, model number 817-30-31ARS, serial number 717413, 29" diameter x 4-1/2" wide, mild steel construction.
266	7302	AAF International W Rotoclone	AAF International W Rotoclone, model number 1656297-008, serial number W120020, control number 300620, size 27, 27" diameter infeed, 2 stage water wash in fan, 25" x 25" air discharge, 12" x 12" slurry discharge, 40 HP electric motor belt drive, 1775 RPM, 230/460 volts, 60Hz, 3 phase, all stainless steel construction, requires slurry discharge.

267



